

#6-0918 BAG-N-WAGON HITCH ADAPTER KIT for SNAPPER YTD & YTH SERIES TRACTORS

INSTALLATION INSTRUCTIONS

This kit is necessary for installing the hitch drawbar equipment provided in the BAG-N-WAGON kit. Install the adapter components as follows:

STEP 1: Remove the two lower hex flange self tapping screws holding the rear cover plate to the frame of the tractor.

STEP 2: Position the hitch adapter on the rear cover plate with slotted holes in upper tube support over the holes for the screws removed in step 1.

NOTE: The lower tube support goes under the drawbar plate.

STEP 3: Turn the two 5/16Cx3/4" hex head capscrews into the lower rear cover plate holes then, reaching inside the drawbar plate and rear cover plate, install the two hex flange locknuts on these capscrews. Do not completely tighten at this time.

STEP 4: Insert the two 5/16Cx1" hex head capscrews into the holes in the drawbar plate and lower tube support plate then install the split lockwashers and hexnuts on the underside. Completely tighten cover plate screws and locknuts then tighten the two drawbar plate/lower tube support fasteners to complete the installation.

#6-0918 KIT PARTS LIST

ITEM	PART NO.	DESCRIPTION
1	4-0639	ADAPTER (Tube & Supports)(1)
2	9-0206*	CAPSCREW, 5/16cx3/4" (2)
3	9-0672*	LOCKNUT, 5/16c Hex Flange (2)
4	9-0209*	CAPSCREW, 5/16cx1" (2)
5	9-0187*	LOCKWASHER, 5/16" Split (2)
6	9-0196*	NUT, 5/16c Hex (2)

* Part of #6-0980 Hardware bag.

SNAPPER® McDonough, GA., 30253 U.S.A.