



DCBL™

SOUND SUPPRESSOR

Contents

- 1 / OVERVIEW**
 - Introduction 4
- 2 / THE BASICS**
 - Anatomy. 5
 - Specifications. 5
 - Safety Warnings 6
 - Legal Warnings 6
- 3 / GET STARTED**
 - Installation. 7
 - Removal 7
- 4 / MAINTENANCE**
 - Disassembly. 8
 - Assembly 8
 - Cleaning. 8
- 5 / NEED SOME HELP?**
 - Warranty. 9
 - Service and Repair 10
 - Contact Information 11

Introduction

EOTECH's DCBL line of premium suppressors are precision-engineered and designed for exceptional sound suppression, recoil mitigation, and operational reliability. Built for the professional user, DCBL suppressors deliver suppression without compromise.

Featuring EOTECH's Vent-Forward Technology, DCBL suppressors actively stabilize internal pressure while reducing blowback and minimizing back pressure to the weapon system. This translates to smoother cycling, reduced carbon buildup, and enhanced shooter control.

Its monolithic, corrosion-resistant construction is built to withstand harsh operational environments, including salt air, extreme temperatures, and prolonged courses of fire.

The Grade 5 Titanium material is treated with a high-temp Cerakote finish for added durability.

Anatomy



Specifications

	DCBL-556	DCBL-762	DCBL-9PCC
Bore Diameter (cal)	0.283	0.39	0.4
Length (suppressor body)	7.1" (180.4 mm)	8" (203.2 mm)	7" (177.8 mm)
Overall Length (with hub/flash hider)	7.9" (200.7 mm)	8.8" (223.6 mm)	7.3" (185.5 mm)
Overall Diameter	1.75" (44.5 mm)	1.75" (44.5 mm)	1.6" (40.7 mm)
Weight (suppressor body)	13.7 oz (387 g)	17.4 oz (492 g)	9.3 oz (263.7 g)
Weight (with hub/flash hider)	19.6 oz (554 g)	22.8 oz (647 g)	13.9 oz (394.1 g)
Material	Grade 5 Titanium		
Finish	High Temp Cerakote		
dB Rating	133.6	132.3	113.5
Full Auto Rated	Not Rated		
Min Barrel Length	10.3"	10.3"	10.3"*

* 10.3" barrel restriction only applies to the 9PCC when used with rifle cartridges

Safety Warnings

ALWAYS ensure your firearm is not loaded before installing or removing the suppressor. Only operate the suppressor system with a known, properly functioning firearm with quality ammunition. ALWAYS check that your ammunition caliber matches the caliber of your suppressor. NEVER disassemble the suppressor beyond what is highlighted in this manual.

The suppressor system can reach extremely hot temperatures. Use caution before handling after use. Avoid contact with skin or clothing when hot. Improper installation or use may result in serious injury or death.

Ensure you are in well ventilated areas before discharging your suppressed firearm. Cleaning your firearms and suppressors, or handling ammunition may result in exposure to lead and other substances, which can cause birth defects, reproductive harm, or other serious physical injury. Wash hands thoroughly after exposure.

Legal Warnings

Suppressors (often referred to as silencers, cans, or mufflers) are controlled under both the National Firearms Act (NFA) (26 U.S.C. §5849 et seq.) and the Gun Control Act (18 U.S.C. §921 et seq.).

Storing an unlocked suppressor at home with a person who is not registered to possess the device may be construed as “constructive possession” by the ATF, which may be punishable by law.

This product is manufactured in the USA and licensed by EOTECH for sale within the USA only. Export of this commodity is strictly prohibited without a valid export authorization from the U.S. Department of State – DDTC and/or the U.S. Department of Commerce - BIS as prescribed in ITAR 22 CFR Part 120-130 and/or EAR 15 CFR Part 774.

Installation

Before installing your suppressor, ensure the firearm is unloaded, the magazine is removed, and the safety is on. Visually check that the chamber is clear.

- Remove current muzzle device or thread protector from barrel.
- Carefully attach KFM flash hider to the barrel at approximately 30 ft/lbs.
- Attach the Hub to the suppressor body by threading the suppressor counter-clockwise until it is hand-tight. Using an Armorer's tool, tighten the Hub to the suppressor body at approximately 35 ft/lbs.
- Carefully, align the Hub threads with the muzzle device threads and slowly engage the threads using a clockwise rotation.
- Once you feel resistance, grip the suppressor firmly and tighten hand-tight or approximately 20 ft/lbs.
- For direct thread suppressors, carefully align the barrel threads to the suppressor threads and slowly engage them using a clockwise rotation. Once you feel resistance, grip the suppressor firmly and tighten hand-tight or approximately 20 ft/lbs.

Removal

Before removing your suppressor, ensure the firearm is unloaded, the magazine is removed, and the safety is on. Visually check that the chamber is clear.

- Ensure your suppressor is cool before touching.
- Wear protective gloves to reduce the exposure of lead.
- If using the KFM muzzle device, turn clockwise (the adapter uses reverse threads).
- Grip the suppressor firmly and turn counter-clockwise.
- Remove it from the barrel threads and replace your muzzle device or thread protector.
- Store your suppressor in a safe, restricted area.

Disassembly

- To disassemble the Hub from the suppressor body, use an Armorer's tool. Align the tool onto the hub, and while holding the suppressor body, crank the tool counter-clockwise to break it from the suppressor body. Continue to turn until it separates from the body.

Assembly

- To assemble the suppressor, align the Hub threads with the suppressor body threads, and slowly begin turning clockwise. Be sure not to cross thread. Once resistance is felt, use the Armorer's tool to tighten firmly (approx. 35 ft/bs).

Cleaning

Before cleaning your suppressor, be sure to wear protective gloves to reduce any lead or contamination. EOTECH recommends cleaning at least every 2,000 rounds. EOTECH suggests cleaning the 9PCC suppressor after every 500 rounds when using pistol ammunition.

- Follow the DISASSEMBLY steps above.
- Because the DCBL suppressors are titanium, be sure to use cleaners that are safe on titanium.
- Clean threads on the suppressor body using a brush or towel.
- To clean the main suppressor body, use a cleaning solvent that breaks down lead and carbon fouling. Follow the instructions of the solvent.
- Once the body is clean, blow it out with a compressor and ensure the inside is free of liquids.
- Follow the ASSEMBLY steps above.

NoBS Warranty

For EOTECH DCBL Suppressors

EOTECH is proud to offer its No BS (NoBS) Lifetime warranty on its premium line of DCBL Suppressors. No BS means exactly that. No BS. EOTECH will repair or replace all issues related to materials and workmanship. We want you to be as confident in your purchase as we are in the quality of our product.

Should your DCBL Suppressor ever experience any issues, we will repair or replace it, as determined by EOTECH, with a comparable product in equal or better condition, free of charge, PERIOD. This warranty extends to the original, registered owner only.

We understand your passion for the sport and your reliance on products that will provide years of dependable use. You can depend on EOTECH products and count on us to take care of you.

This warranty does not apply to the following:

- Theft, loss, neglect, or vandalism.
- Abuse, misuse, improper installation and modification, alterations, abnormal use, or accidents.
- Use of ammunition types or barrel lengths not intended for the suppressor.
- Cosmetic damage that does not affect the product's use, operation or performance, as determined by EOTECH.
- Any defect or damage caused by repairs or services not performed by EOTECH.
- EOTECH products not in the DCBL line of Suppressors.
- Damage related to full-auto firing.

The warranty provided herein shall be the sole and exclusive warranty. There shall be no other warranties express or implied including any implied warranty of merchantability or fitness for a particular purpose or any other obligation on the part of EOTECH with respect to DCBL suppressors covered by this warranty. EOTECH shall have no liability for any incidental, consequential, or special damages.

Service and Repair

- Visit the manufacturer's website at eotechinc.com.
- Navigate to the Help Center to complete the Return Authorization Request Form. EOTECH will provide detailed instructions on how to return your optic for repair.
- Contact EOTECH's Customer Service department by calling 888-EOTHOLO (888-368-4656) or submit a request online at eotechinc.com.

PRO TIP: *Do not ship the suppressor without a Return Authorization Number and ATF FORM. — this will severely delay the turnaround time on repair or replacement.*

Contact Information

CUSTOMER SERVICE/REPAIR

888-368-4656

eotechinc.com/help-center

RA# REQUEST WEB ADDRESS

eotechinc.com/help-center

SHIPPING ADDRESS

EOTECH

110 Kapsia Way

Clarksville, TN 37040 USA

SCAN FOR
PRODUCT
REGISTRATION



SCAN FOR
WARRANTY
INFORMATION





**Thank you for purchasing an
EOTECH Sound Suppressor**

SP2501 REV A | NOVEMBER 2025
Proudly Made in the USA

EOTECHINC.COM