

EPSON®

INK JET PRINTER

STYLUS® C82N

The ultimate network solution for high-speed performance.

The EPSON Stylus C82N, with out-of-the-box networking capabilities, offers incredible speed and performance, whether you're printing photos, presentations or text. You get phenomenal plain paper print outs. And, EPSON DuraBrite™ Inks mean the results are both water- and light-resistant.

Key Features

- **Out-of-the-box network printing**

Ensures easy operation with most 10/100 Base-TX network configurations

- **Water- and light-resistant DuraBrite Inks**

Light resistance up to 80 years on specialty papers and 70 years on plain paper*

- **Up to 22 ppm black text and 11 ppm color printing****

- **Cost-saving individual ink cartridges**

- **Supports multiple operating systems**

Supports Windows® 3.x/95/98/Me/NT/2000/XP, Novell NetWare, Linux, UNIX, Macintosh® OS 7.x or later/OS X; enables users to access an Epson printer without complicated configuration setup schemes

- **Includes EpsonNet printer management utilities**

Includes EpsonNet WebManager and EPSON Status Monitor to manage printers and job status on the network



DURABrite
INK



EPSON®

INK JET PRINTER

STYLUS® C82N

SPECIFICATIONS

Printing Method

Drop-on-demand Micro Piezo® ink jet technology,
Optimized for plain paper desktop color printing

DuraBrite Ink

Water-resistant on all media including plain paper,
Light-resistant up to 80 years*
Individual ink cartridges

Resolution (dots per inch)

Up to 5760 x 1440 optimized dpi on various papers, in Photo RPM™ mode

Print Speed**

Black	Up to 22 ppm
Color	Up to 11 ppm

Photo

4" x 6" photo on EPSON Glossy Photo Paper in Photo Mode, 1 min 19 sec

8" x 10" photo on EPSON Glossy Photo Paper in Photo Mode, 2 min 35 sec

Printer Language

EPSON ESC/P® Raster; EPSON Remote

Client Operating Systems

Windows 95/98/2000/Me/XP/NT 4.0

Macintosh 7.x or later, OS X, OS/2

UNIX and Linux

Network Operating Systems

NetWare 3.1x or later, Windows NT 4.0, Windows 95, Me, XP peer to peer,

Windows 98 peer to peer, Windows 2000, OS/2 LAN Server, OS/2 Warp Connect,

Solaris 2.4 or later, Sun OS 4.1.4 or later, AIX 3.2.5 or later, HP-UX 9.05 or later, SCO

UNIX 4.2 or later

Frame Type

802.2, 802.3, 802.2 SNAP, Ethernet II

Protocols

TCP/IP

LPR/LPD, FTP, Telnet, IP, ICMP, UDP, HTTP, SNMP, DHCP,
ARP, RARP, BOOTP, IPP

Novell NetWare

NDS, Bindery, IPX, SPX, RIP, IP, SAP, NCP, NDPS

Apple® Ethernet

ELAP, AARP, DDP, NBP, ZIP, RTMP, ATP, PAP

Windows/LAN Server

NetBEUI/NetBIOS

Standard Interfaces

USB, Parallel (IEEE 1284)

Paper Capacity

Input paper tray 150 sheets/15 envelopes

Dimensions and Weight (L x W x H)

23.3" x 18.5" x 12.4" with trays extended; 11.41 lb

Ink Cartridges

Black ink yield 1240 pages text (ISO/IEC 10561 letter pattern);
870 pages graphics (5% coverage)

Color ink yield 420 pages (15% coverage)

Shelf life 2 years from production date

Warranty

Standard one-year limited warranty including EPSON Exchange program
(U.S. and Canada only)

* Light resistance rating based on accelerated testing of prints displayed indoors, under glass. Actual print stability will vary according to image, display conditions, light intensity, paper, humidity and atmospheric conditions. Ratings based on ink only; some papers may discolor over time. Epson does not guarantee the longevity of prints. For maximum print life, display all prints under glass or lamination or properly store them.

** Pages per minute based on text memo in Economy Mode on plain paper. Additional processing time may vary based on system configuration, software application and page complexity.

**EPSON**www.epson.com

Epson America, Inc.
3840 Kilroy Airport Way,
Long Beach, CA 90806

Epson Canada, Ltd.
3771 Victoria Park Avenue
Toronto, Ontario M1W 3Z5

Epson Latin America, Inc.
6303 Blue Lagoon Drive, Suite 195
Miami, FL 33126

Specifications and terms are subject to change without notice. EPSON, EPSON Stylus and Micro Piezo are registered trademarks of Seiko Epson Corporation. DuraBrite and RPM are trademarks of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. © Copyright 2002 for Epson America, Inc. CPD-15088 25K 9/02 WP