

PowerLite® 1825

Multimedia Projector



Powerful wireless
performance.

Features/Benefits

- Deliver brilliant presentations, even in well-lit rooms, with 3500 lumens
- Project video wirelessly with 802.11a/b/g via Windows Vista® or included EasyMP® software
- Monitor and control installed projectors, or make a presentation over the LAN, with included software
- Set up in six seconds with Quick Setup's automatic image adjustments
- Get amazing color, detail and reliability with 3-chip 3LCD technology
- Send video and audio wirelessly in MovieSending Mode
- Enjoy added positioning flexibility with 1.6x zoom ratio
- Use remote-free power control on installed units with direct power on/off
- Easily access and replace the lamp and air filter, even if the projector is ceiling mounted
- Display most image files without a computer via CompactFlash® or USB memory device



Ordering Information

Product Name	Product Code	UPC
PowerLite 1825	V11H274020	0 10343 86734 5
Replacement lamp	V13H010L40	0 10343 86282 1
Replacement air filter	V13H134A08	0 10343 85123 8

Epson PowerLite 1825 Specifications

Projection System

Epson 3-chip 3LCD technology

Projection Method

Front/rear/ceiling mount

LCD

Driving Method

Epson Poly-silicon TFT Active Matrix

Pixel Number

786,432 dots x 3 (1024 x 768) LCDs

Native Resolution

XGA

Aspect Ratio

4:3 (supports 16:9)

Pixel Arrangement

Cross-stripe

Projection Lens

Type

Manual focus/zoom

F-number

1.75 – 2.42

Focal Length

24 – 38.2 mm

Zoom Ratio

Optical zoom 1.0 – 1.6

Lamp

Type

210 W UHE

Life*

2500 hours (High Brightness Mode)

3000 hours (Low Brightness Mode)

Screen

Throw Ratio Range

1.46" – 2.39"

Size (projected distance)

30" – 300" (2.7' – 48.2')

Keystone Correction

Automatic: Vertical: ± 45 degrees

Manual: Vertical: ± 45 degrees

Horizontal: ± 30 degrees

Brightness (High Brightness Mode)

Up to 3500 lumens (ISO 21118 Standard)

Contrast Ratio (High Brightness, Game Mode)

Up to 500:1

Brightness Uniformity (typical)

90%

Color Reproduction

16.7 million colors

Dimensions (W x D x H)

Including Feet

13.6" x 10.1" x 3.7"

Excluding Feet

13.6" x 10.1" x 3.4"

Weight

6.9 lb/3.1 kg

Effective Scanning Frequency Range

Pixel Clock

13.5 MHz – 162 MHz

Horizontal

15 KHz – 99 KHz

Vertical

50 Hz – 120 Hz

Remote Control

Features

Source search selection, power, aspect resize, color mode, volume, e-zoom, A/V mute, freeze, menu, page up and down, help, auto, enter, esc and pointer functions

Operating Angle

Right/left ± 30 degrees

Upper/lower ± 15 degrees

Operating Distance

19.7 ft (6 m)

Display Performance

Native

1024 x 768

Resize

640 x 480

800 x 600

1280 x 1024

1400 x 1050

1600 x 1200

Video I/O

Display Performance

NTSC: 560 line

PAL: 560 line

(depends on observation of the multi burst pattern)

Input Signal

NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/

SECAM

SDTV: 480i, 480p; HDTV: 720p, 1080i

Interfaces

Computer/component video: Mini D-sub HD 15 pin x 2

S-video: Mini DIN x 1

Composite video RCA x 1

Audio in x 3 (RCA (L & R) x 1, mini stereo x 2)

Variable audio out: mini stereo x 1

USB connector Type B x 1 (for mouse/keyboard

control, USB display)

USB connector Type A x 1 (for USB memory device)

CompactFlash x 1 (3.3v)

LAN networking: RJ-45 x 1

Serial: RS-232c x 1

Monitor out: Mini D-sub 15 pin x 1

Other Features

Audio Output

5 W monaural

Audio Signal

500 m Vrms/47K ohm

Operating Temperature

41 ° to 95 °F (5 ° to 35 °C)

Power Supply Voltage

100 – 240 V ±10%, 50/60 Hz AC

Power Consumption

306 W, 12 W standby (network on),

2.6 W standby (network off)

Fan Noise

37 dB (High Brightness Mode)

32 dB (Low Brightness Mode)

Security

Kensington®-style lock provision, anchor (metal) bar for security lock or cable

Support — The Epson Connection™

Pre-sales Support

U.S. and Canada

800-463-7766

Internet Web Site

www.epson.com

Projector resources available at

presentersonline.com

Service Programs

Two-year limited warranty, 90-day lamp warranty, Epson Road Service Program and Epson PrivateLine® dedicated toll-free support (U.S. and Canada only)

Contents

Wireless LAN module, power cable, computer cable, projector remote control, soft carrying case, batteries, user manual CD, EasyMP software CD, Quick Setup Sheet, PrivateLine support card, password protection sticker and security screw

Accessory Part Numbers

Replacement remote control	1452589
Universal projector ceiling mount	ELPMBPJF
Advanced projector ceiling mount	
with precision gear	ELPMBPRG
High security projector ceiling mount	ELPMBATA
Adjustable suspended ceiling	
channel kit	ELPMBP01
False ceiling plate kit	ELPMBP02
Structural round ceiling plate	ELPMBP03
Adjustable extension column	
(pipe) 6"–9"	ELPMBC01
Security flex foot kit	ELPMBF01
Distribution amplifier	ELPDA01
Component to VGA video cable	ELPKC19
S-video cable	ELPSV01
Wheeled soft case	ELPKS62
Soft shoulder case for projector	
and laptop	ELPKS61
Molded hardshell case	ELPKS58
50" portable screen	ELPSC06
60" portable pop-up screen	ELPSC07
80" portable pop-up screen	ELPSC08
Duet™ screen	ELPSC80
Image presentation camera	(ELPDC05)
	V12H162020
Kensington security lock	ELPSL01

* Lamp life results will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time.

Packaging Specifications

PowerLite 1825

Dimensions 14.4" x 19.8" x 9.0" (W x D x H)

Weight 13.9 lb

Replacement Lamp

Dimensions 5.5" x 6.3" x 5.6" (W x D x H)

Weight 0.8 lb (approx.)

Master Carton

Dimensions 13.1" x 28.4" x 6.8" (W x D x H)

Weight 10.1 lb (approx.)

Units Per Master Carton 10

Replacement Air Filter

Dimensions 4.1" x 11.4" x 1.9" (W x D x H)

Weight 0.35 lb

Master Carton

Dimensions 11.8" x 18.9" x 4.7" (W x D x H)

Weight 4.4 lb

Units Per Master Carton 10



Epson America, Inc.

3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.

3771 Victoria Park Avenue, Toronto, Ontario M1W 3Z5

www.epson.com

www.epson.ca

Specifications and terms are subject to change without notice. Epson and EasyMP are registered trademarks and Epson Exceed Your Vision is a trademark of Seiko Epson Corporation. PowerLite and PrivateLine are registered trademarks, Duet is a trademark, and Epson Connection and Epson PresentersOnline are service marks of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2008 Epson America, Inc. CPD-24888R1 3/08 PDF