# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

# MODEL G0723 1/4 HP BENCHTOP OSCILLATING SANDER

**Product Dimensions:**

| | |
|---|---|
| Weight | 46 lbs. |
| Width (side-to-side) x Depth (front-to-back) x Height | 22-7/8 x 18 x 20 in. |
| Footprint (Length x Width) | 22-1/4 x 16-3/4 in. |

**Shipping Dimensions:**

| | |
|---|---|
| Type | Cardboard Box |
| Content | Machine |
| Weight | 56 lbs. |
| Length x Width x Height | 25 x 20 x 22 in. |

**Electrical:**

| | |
|---|---|
| Power Requirement | 120V, Single-Phase, 60 Hz |
| Prewired Voltage | 120V |
| Full-Load Current Rating | 2.6A |
| Minimum Circuit Size | 15A |
| Connection Type | Cord & Plug |
| Power Cord Included | Yes |
| Power Cord Length | 6 ft. |
| Power Cord Gauge | 18 AWG |
| Plug Included | Yes |
| Included Plug Type | NEMA 5-15 |
| Switch Type | Paddle Safety Switch w/Removable Key |

**Motors:**

**Main**

| | |
|---|---|
| Horsepower | 1/4 HP |
| Phase | Single-Phase |
| Amps | 3.5A |
| Speed | 1725 RPM |
| Type | TEFC Capacitor-Start Induction |
| Power Transfer | Direct Drive |
| Bearings | Shielded & Permanently Lubricated |
| Centrifugal Switch/Contacts Type | N/A |

**Main Specifications:**

**Spindle Sander Info**

| | |
|---|---|
| Sanding Drum Diameters | 1/2, 3/4, 1, 1-1/2, 2, 3 in. |
| Sanding Drum Length | 4-1/2 in. |
| Spindle Speed | 1725 RPM |
| Spindle Oscillation | 30 SPM |
| Stroke Length | 1 in. |
| Table Length | 18 in. |
| Table Width | 18 in. |
| Table Thickness | 11/16 in. |
| Table-to-Floor Height | 15-1/2 in. |
| Spindle Shaft Diameter | 1/2 in. |
| Number of Table Inserts | 5 |
| Included Sanding Sleeve Grit Size | 100 |


*The information contained herein is deemed accurate as of 11/16/2026 and represents our most recent product specifications. Due to our ongoing improvement efforts, this information may not accurately describe items previously purchased.*

**Construction Materials**

| | |
|---|---|
| Base | Plastic |
| Table | Cast Iron |

**Other Related Info**

| | |
|---|---|
| Dust Port Size | 2 in. |

**Other Specifications:**

| | |
|---|---|
| Country of Origin | Taiwan |
| Warranty | 1 Year |
| Approximate Assembly & Setup Time | 15 Minutes |
| Serial Number Location | ID Label |
| Certified by a Nationally Recognized Testing Laboratory (NRTL) | Yes |

**Features:**

A spacious 18 inch table leaves plenty of room to navigate while smoothing curved edges.
Sanding drums store neatly in the base for easy, organized access.
Space-saving benchtop style.
ON/OFF paddle switch with removable key.
Includes 6 sanding sleeves from 1/2" to 3" in diameter.