MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0920 22" VARIABLE-SPEED OPEN-ENDED DRUM SANDER

Product Dimensions:

Weight..... 307 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 42-1/2 x 43-1/2 x 61 in.
Footprint (Length x Width)..... 23-1/2 x 32-1/2 in.

Shipping Dimensions:

Carton #1

Type..... Cardboard Box
Content..... Machine
Weight..... 236 lbs.
Length x Width x Height..... 45 x 26 x 26 in.
Must Ship Upright..... Yes

Carton #2

Type..... Cardboard Box
Content..... Stand
Weight..... 105 lbs.
Length x Width x Height..... 34 x 27 x 14 in.
Must Ship Upright..... Yes

Electrical:

Power Requirement..... 230V, Single-Phase, 60 Hz
Full-Load Current Rating..... 8.5A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 60 in.
Power Cord Gauge..... 14 AWG
Plug Included..... Yes
Included Plug Type..... 6-15
Switch Type..... Control Panel w/Magnetic Switch Protection

Motors:

Main

Horsepower..... 2 HP
Phase..... Single-Phase
Amps..... 7.5A
Speed..... 1720 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer ..... Direct
Bearings..... Sealed & Permanently Lubricated
Centrifugal Switch/Contacts Type..... External

The information contained herein is deemed accurate as of 11/16/2026 and represents our most recent product specifications. Due to our ongoing improvement efforts, this information may not accurately describe items previously purchased.

Feed

Horsepower	50W
Phase	Single-Phase
Amps	1A
Speed	2200 RPM
Type	Universal
Power Transfer	Direct
Bearings	Sealed & Permanently Lubricated

Main Specifications:

Operation Information

Number of Sanding Heads	1
Maximum Board Width	21-1/4 in.
Minimum Board Width	2 in.
Maximum Board Thickness	5 in.
Minimum Board Thickness	1/4 in.
Minimum Board Length	9 in.
Sandpaper Speed	2300 FPM
Conveyor Feed Rate	0 - 10 FPM
Sandpaper Length	127-1/2 in.
Sandpaper Width	3 in.

Drum Information

Infeed Sanding Drum Type	Aluminum
Infeed Sanding Drum Size	5 in.

Construction

Conveyor Belt	Rubber
Body	Steel
Paint Type/Finish	Powder Coated

Other Related Information

Floor To Table Height	36-1/4 in.
Sanding Belt Tension	Spring Loaded
Number of Pressure Rollers	2
Pressure Roller Type	Steel
Pressure Roller Size	3/4 in.
Conveyor Belt Length	46 in.
Conveyor Belt Width	22 in.
Belt Roller Size	1-3/4 in.
Number of Dust Ports	1
Dust Port Size	4 in.

Other Specifications:

Country of Origin	Taiwan
Warranty	1 Year
Approximate Assembly & Setup Time	30 Minutes
Serial Number Location	ID Label

Features:

Spring-Loaded Sanding Belt Tension/Sandpaper
Industrial-Duty Rubber Conveyor Belt
4" Dust Port w/Dust Hose Hook
Variable-Speed Conveyor
5" Aluminum Computer-Balanced Sanding Drum
Drum Lifting and Lowering System with Precision DRO
Push Button Circuit Breaker for Easy Reset