



593 North Wright Brothers Drive | Salt Lake City | Utah | USA | 84116-2887
Phone 801-363-2990 | Fax 801-537-1470 | www.hoyt.com



Follow us on Twitter!
[www.twitter.com/hoytarcheryinc](https://twitter.com/hoytarcheryinc)



Like us on Facebook!
www.facebook.com/HoytTargetArchery
www.facebook.com/HoytBowhunting



Follow us on Instagram!
www.instagram.com/HoytTargetArchery
www.instagram.com/HoytBowhunting



Subscribe to us on YouTube!
youtube.com/hoytarcheryinc


HOYT COMPOUND BOW LIMITED LIFETIME WARRANTY

All Hoyt compound bows are guaranteed against manufacturing defects in materials or workmanship to the original owner on all risers, limbs, limb pockets, and eccentrics for the life of the product.*

*For all warranty details see page 16 of this Owner's Manual or hoyt.com. Bows purchased over the Internet or through mail order void all warranty.



Official Bow Partner of World Archery



THE BOWS OF CHAMPIONS.



TARGET COMPOUND BOW
OWNER'S MANUAL

WELCOME TO TEAM HOYT.

Congratulations on the purchase of your new Hoyt bow. We are excited and grateful to have you as a part of Team Hoyt. You will be pleased to know that you have purchased the most technologically advanced and dependable bow on the market. Only the finest components go into every Hoyt bow along with over 85 years of industry leading experience in bow technology and manufacturing. With proper use and some basic maintenance, your new bow will provide you with years of great shooting and dependability.

Archery is a very enjoyable form of recreation for people of all ages and abilities. It is important to note that archery equipment, when not used properly, can create a dangerous situation, including death and serious personal injury for the archer or those around them. It is up to you to be a responsible archer, protect both yourself and others when enjoying this great sport. Whether you are an experienced archer or have never shot a bow, you must **READ THIS ENTIRE MANUAL CAREFULLY** before using your bow. Following all warnings and instructions contained in this manual will help ensure you and others have the safest and most enjoyable shooting experience possible. Keep this owner's manual handy and reference it often. Should you lose this manual you can find a current manual online at www.hoyt.com. Good luck and safe shooting!

GET SERIOUS. GET HOYT.



BOW OWNER'S PERSONAL INFO

Fill in the following personal bow record for your reference.

Bow Serial Number: _____
(See page 30 for information on where your bow serial number is located.)

Hoyt Bow Model: _____

Purchased From: _____

Purchase Date: _____

Draw Length: _____ (in.) Draw Weight: _____ (lb.)

String Length: _____ (in.) Buss Cable Length: _____ (in.)

Control Cable Length: _____ (in.)

IMPORTANT!
A copy of your sales receipt is required for warranty purposes.

The sales receipt, as well as the serial number, is your proof of date-of-purchase. Proof of date-of-purchase will be required if your bow ever needs warranty service.



TABLE OF CONTENTS/WARNINGS

Bow Owner's Personal Info 1

Important Safety Information 2

Compound Bow Terminology 5

Bow Setup 7

Accessory Selection 7

Draw Length 7

Draw Weight 8

Centershot Alignment 8

Nock Point Location 8

Fine Tuning 8

Tuning for Broadheads 8

Bow Maintenance 8

Strings and Cables 8

LimbShox and String Silencers 9

StealthShot String Suppressor 9

Paint and Finish 9

Cam Lubrication 9

Bow Press Usage 10

ZT Cable Guard 11

Prevail Cable Guard Bar 12

Standard Cable Guard Installation 12

Standard Cable Slide Installation 12

Draw Length Adjustment 12

Factory Settings 14

Cam Synchronization 14

Cam Let-Off Adjustment 15

Back Wall Adjustment 15

Axle E-Clip Installation Criteria 15

Prevail and HyperEdge Modular Grip System 15

Locating Your Serial Number 15

Hoyt Carbon Riser Precautions and Information 15

Warranty 16

This manual contains several safety warnings and instructions preceded with **⚠️WARNING**, **⚠️CAUTION** or **📌NOTICE**. These signal words are designed to draw attention to important safety information. **⚠️WARNING** indicates a hazardous situation which, if not avoided, could result in death or serious personal injury. **⚠️CAUTION** indicates a hazardous situation, which, if not avoided, could result in moderate or minor personal injury. **📌NOTICE** addresses safety practices not related to personal injury.

⚠️WARNING

READ THIS MANUAL CAREFULLY BEFORE HANDLING OR USING YOUR HOYT BOW. YOU ARE RESPONSIBLE FOR ARCHERY SAFETY.

Read and follow all warnings and guidelines for safe operating parameters at www.hoyt.com/safetyandwarnings

The warnings contained within this owner's manual were current at time of printing. For the most up to date list of warnings please visit:
www.hoyt.com/safetyandwarnings

⚠️WARNING: Always read the warning labels and manufacturer's instructions of all products being used in conjunction with a Hoyt bow, including but not limited to all archery accessories and components directly attached to the bow or used in conjunction with the bow such as targets, arrows, broadheads, release aids, etc.

⚠️WARNING: It is critical that your bow is set up and functioning within the bow's required safe operating parameters prior to use. Hoyt recommends that only a Genuine Hoyt Retailer setup and inspect your archery equipment to ensure that it is set up within the bow's safe operating parameters. (see page 6 for definition of Hoyt Bow Safe Operating Parameters).

⚠️WARNING: To avoid severe personal injury, to yourself or bystanders, as well as damage to your bow, it is of the utmost importance that only Hoyt approved bow presses should be used to press Hoyt bows. **STANDARD BOW PRESSES CANNOT BE USED** and may result in bow failure and personal injury. Hoyt recommends that only Genuine Hoyt Retailers press your bow. See page 10 for guidelines on pressing Hoyt bows.

⚠️WARNING: Carefully inspect your bow before each use. Before you handle or shoot your bow, carefully inspect the condition of your bow, accessories, arrows,

and your release aid to ensure they are in good and proper working condition. Any suspected damage to your bow should be inspected by Hoyt or a Genuine Hoyt Retailer for possible repair or replacement.

⚠️WARNING: Before you handle or shoot your bow or other archery products, Hoyt recommends that you be trained and instructed in proper use by a certified archery coach. Sources such as USA Archery (www.teamusa.org/usa-archery/coaching/find-an-instructor-or-coach), the National Field Archery Association **NFAA** (www.nfaausa.com/state-organizations), and The Archery Trade Association **ATA** (www.archery360.com) have contact information for certified archery coaches in your area. Other archery associations in your area or country may also have suitable programs.

⚠️WARNING: An adult should always supervise minors when they are handling or shooting a bow.

⚠️WARNING: Never use alcohol or drugs while handling or shooting your bow.

⚠️WARNING: Always wear safety glasses when handling or shooting your bow.

⚠️WARNING: Never let go of the bow handle while drawing the bow, holding the bow at full draw, or shooting the bow. It is important that you are able to maintain a consistent and secure grip on the bow handle without slippage of your hand on the bow grip. Use of items such as hand lotions, sunscreens, and bug repellents may limit your ability to maintain control of the grip.

⚠️WARNING: Always ensure that the area around your bow is clear of any and all obstructions to prevent items from being caught in the moving parts of the bow. When shooting your bow, never wear loose clothing, jewelry, or other items worn on your body that may get caught in the bow or bow string when the bow is shot.

⚠️WARNING: Never point or aim a bow at another person. Be sure of your target and what lies beyond. Never shoot arrows straight up into the air. Make sure that the path from where you are shooting to the target and beyond is free from people and obstructions. The view that you see when looking through your sight while shooting (the sight picture) may not clearly show the trajectory path of the arrow.

⚠️WARNING: Never dry fire your bow. To dry fire your bow, means to shoot the bow without an arrow. Never try drawing a bow that is too heavy for your strength or that does not fit your draw length as this could lead to an unintentional dry fire. A dry fire could cause your bow to break and cause death or serious injury to you or others. If your bow is dry-fired there could be both seen and unseen damage and it should be returned to Hoyt or taken to a Genuine Hoyt Retailer for inspection before any further use.

⚠️WARNING: Never loosen your limb weight adjustment bolts more than 8 turns as it could cause the bow to violently disassemble. (Note: 10 turns is acceptable on certain youth bows. Consult Hoyt Customer Service for details.)

⚠️WARNING: Do not perform any maintenance, adjustments, or have any work performed of any kind on any part of your bow while drawing or during any other part of the shooting cycle. Do not allow others to work on or touch any part of your bow during the shooting cycle.

⚠️WARNING: Never shoot a bow with the incorrect arrow size (spine) or the incorrect arrow length. Shooting an incorrect arrow size or length could cause your arrow to break and cause serious injury to you or others. Refer to the specific arrow manufacturer's arrow selection chart to select the correct arrow size and length for your setup.

⚠️WARNING: Never shoot an arrow weighing less than five grains for every pound of peak draw weight of your bow. For example: If your bow's peak draw weight is 70 pounds, do not shoot an arrow weighing less than 350 grains. Shooting an arrow below five grains per pound of peak draw weight could cause your bow to break and cause death or serious injury to you or others.

⚠️WARNING: Never shoot a damaged arrow. Before each shot, inspect your arrows for damage. See the specific arrow manufacturer's warnings and instructions on proper arrow inspection methods. Discard all damaged arrows.

⚠️WARNING: Never mechanically alter or modify your bow. Drilling holes, cutting, filing, or sanding are examples of mechanically altering your bow which will likely cause the bow to break and could cause death or serious injury.

⚠️WARNING: Never alter your Hoyt bow from its original factory configuration. Changing your bow's cams, limbs, or other components from its original equipped and configured assembly could cause your bow to break and could cause death or serious injury.

⚠️WARNING: Never draw or shoot a bow with frayed, worn, or damaged string or cables as they could break. Frayed, worn, or damaged bowstrings or cables should be immediately replaced by Hoyt or a Genuine Hoyt Retailer before the bow is used. Carefully inspect the string and cables each time before shooting your bow. Hoyt recommends that you replace your string and cables after 2,000 shots or after two years, whichever comes first.

⚠️WARNING: Never draw or shoot your bow without all string accessories (peep sight, kissers button, nock points, D-Loop, string silencers, string weights, and speed weights) properly installed and secured to the string. Do not use brass or other metal clamp-on nocking point or string weight devices. Hoyt recommends that only a Genuine Hoyt Retailer install all string accessories. (see page 6 for definition of Hoyt Bow Safe Operating Parameters).

⚠️WARNING: Never expose your string or cables to sharp objects such as knives or broadheads, or direct heat sources such as open flame or extremely hot objects as they could easily cut or cause the string and/or cables to break.



⚠️WARNING: Never draw a bow with mismatched or missing cam modules, module screws and/or set screws. Never draw a bow with a missing or incorrectly installed draw stop peg. Never remove the cam control cable peg. Be sure to thoroughly check these areas of the cam with an allen wrench to ensure they are fully tightened and that modules are not mismatched.

⚠️WARNING: While servicing Hoyt compound bows, it may be necessary to remove and reinstall e-clips on the ends of the axles. It is critical that the e-clips are installed correctly. If e-clips are not installed correctly, it is likely that one or more of the limbs will work their way off the end of the axle, causing the bow come apart and may result in injury to user or bystanders. (See page 15 for installation instructions)

⚠️WARNING: Do not draw or shoot bow without the cable guard, cable slide and/or rollers properly installed, adjusted and tightened.

⚠️WARNING: Only use genuine Hoyt manufactured replacement parts. Only Hoyt or a Genuine Hoyt Retailer should perform replacement of damaged parts. Hoyt recommends that all maintenance or service that requires the use of a bow press only be

performed by a Genuine Hoyt Retailer. The use of an improper style bow press on your Hoyt bow or the incorrect use of any bow press on your bow may result in severe damage to the bow (see page 10 for definition of an appropriate style press for Hoyt bows).

⚠️WARNING: Never expose your Hoyt carbon bow to any solvents or lubricants as the structure could become weakened.


⚠️WARNING: Never expose your carbon bow to direct impact. If impact occurs, return your bow to Hoyt or take your bow to a Genuine Hoyt Retailer for inspection and required repair.

⚠️WARNING: Never expose your bow to extreme heat or prolonged moisture. Damage can occur to your bow from heat exposure, prolonged exposure to moisture and improper storage.

⚠️WARNING: This warning is given in compliance with California State Prop 65. This product contains chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.

COMPOUND BOW TERMINOLOGY

- 1 Top Cam
- 2 LimbShox
- 3 Limbs
- 4 Limb Pocket
- 5 Riser
- 6 Sight Window
- 7 Shelf
- 8 Grip
- 9 Stabilizer Bushing
- 10 Limb Weight Adjustment Bolt
- 11 Rockers
- 12 Bottom Cam
- 13 Axle
- 14 Control Cable
- 15 Stealth Shot
- 16 ZT Cable Guard, Adjustable Cable Guard or Cable Guard with Cable Slide*
(*depends on model of bow)
- 17 Shooting String
- 18 Split Yoke Buss Cable



REQUIRED SAFE OPERATING PARAMETERS

⚠️WARNING: It is critical that your bow is set up and functioning within the bow's required safe operating parameters prior to use. Hoyt recommends that only a Genuine Hoyt Retailer setup and inspect your archery equipment to ensure that it is set up within the bow's safe operating parameters. After your bow is set up within the bow's required safe operating parameters, the bow should be tuned for improved accuracy based on your shooting style and form, the arrow type and size used, and all other accessories used. See page 7 for tips and basic tuning procedures.

CAM SETTINGS

Both the top and bottom cams must be of the same cam type and size. Most Hoyt compound bows use a cam system that can be adjusted to change the bow's draw length. If your cams have an adjustable module/system for draw length adjustments, all screws or other fasteners used to attach the modules must be tight and securely in place. For cams with replaceable draw length modules, both the top and bottom modules must be a matching set and the cable draw stop peg must be in the correct position that matches with the module setting (see **photo A**). For cams that have a rotating type module for draw length adjustment, both the top and bottom cam modules must be a matched set and rotated and set in the same position (see **photo B**).

For more information on specific types of cams, settings, adjustments, etc., see page 12




Photo A




Photo B




Photo C

LIMB WEIGHT ADJUSTMENT BOLT SETTINGS

All Hoyt compound bows have an adjustable limb system that allows the bow's peak draw weight to be adjusted within the specific bow's available range. Your bow's peak draw weight can be adjusted within the bow's range by turning the bow's top and bottom limb weight adjustment bolts equally (see **photo C**). Never turn your bow's limb weight adjustment bolts out more than 8 full

turns as the bow will become disassembled. (Note: On Ignite model bows only, limb weight adjustment bolts can be loosened up to 10 turns.) Always ensure that both your top and bottom limb weight adjustment bolts are adjusted and set at equal positions. For more information on proper draw weight adjustment, see page 8.

ATTACHED BOW ACCESSORIES

Your Hoyt bow is equipped with various accessory mounting locations to allow accessories such as sights, quivers, arrow rests, and stabilizers to be attached to your bow. When attaching an accessory to your bow, follow all accessory mounting and use instructions provided by the accessory manufacturer. Ensure that all accessories are specifically right handed or left handed to match your bow where applicable and that all mounting hardware is securely tightened. Ensure that all attached accessories are clear of string and arrow flight path when the bow is shot.

ARROW REST SETTING

There are many different arrow rest designs and styles. Ensure the arrow rest is right handed or left handed based on your bow. On all Hoyt bows, arrow rests should be positioned on your bow so that your arrow fletchings completely clear the bow riser when the bow is shot. For all Hoyt bows, the required safe operating position of the arrow rest when setup within the safe operating parameters is with the center of the arrow between 5/8" and 1" from the bow's riser at the rest mounting location (see **photo D**). Always follow and use the specific arrow rest manufacturer's instructions for correctly setting up the arrow rest for proper function and tuning.



Photo D




Photo E

D-LOOPS AND NOCKING POINTS

All bows require the use of a D-Loop or a nocking point device to properly locate the arrow onto the bow string in relationship to the arrow rest. For all Hoyt bows, the required safe operating position of the D-Loop or the nocking point device is when the arrow is attached to the bow string and resting on the arrow rest, the arrow will be at a right angle to the bow string plus or minus 3/16"

(see photo E). Never use a brass or other metal clamp-on nocking point device with your Hoyt bow. Only use a high quality archery serving material for installing a "tied-on" nocking point (see photo F for an example of a "tied-on" nocking point). Only use a high quality archery D-Loop material for installing a D-Loop (see photo F for an example of a D-Loop). Ensure that the "D-Loop" or "tied-on" nocking point is securely attached to the bow string and cannot move on the string or come off of the string during shooting.




Photo F

OTHER STRING ACCESSORIES

Other string accessories such as peep sights, string silencers, kissers buttons or any other devices attached to the bow string or cables of your bow must be installed in such a way that they cannot move or come off of the bow string or cables during shooting. Hoyt recommends that only a Genuine Hoyt Retailer install and set-up any string accessories on your Hoyt bow.


COMPOUND BOW SETUP, TUNING AND MAINTENANCE

ACCESSORY SELECTION

Hoyt Archery manufactures a broad selection of archery gear and accessories. Your Genuine Hoyt Retailer can help you choose, install and tune the proper gear and accessories for your style of shooting. Do not modify your bow to accommodate an accessory that is not meant for your bow.

DRAW LENGTH

Draw length is determined by many variables. Your Genuine Hoyt Retailer is trained in properly fitting the bow to your size and style of shooting. Hoyt offers two basic types of adjustable cams to fit archers needs; rotating inner-cam module cams and exchangeable module cams. Draw length is measured in inches using the ATA



CUSTOM ACCESSORIES

Take your bow to the next level. Advanced accessories from Hoyt allow you to dial-in your shot with a look and feel that's all you.

**DFX and DFX Turbo Cams are equipped with a draw stop peg that must be located in the corresponding module position.*

COMPOUND BOW SETUP, TUNING AND MAINTENANCE (continued)

(Archery Trade Association) standard method. Measure from the deepest part of the grip or to the center of the Berger Button (rest mounting hole) plus 1 3/4". See page 12 for detailed instructions on adjusting your bow's draw length.

DRAW WEIGHT


Weight adjustments can easily be made by turning the weight adjustment bolt clockwise to increase weight or counter clock-wise to decrease weight. To ensure your tiller stays equal always turn the top and bottom adjustment bolts in equal amounts. Hoyt bows are capable of being reduced to 10 pounds lower than the peak weight. For example, a Hoyt bow with a 60 lb. max weight can be adjusted to as low as 50 lbs. Do not let out or loosen your limb bolts more than 8 turns (10 turns on Ignite Series bows) doing so may cause limbs to pop out during adjustment or while shooting, causing serious injury to you or a bystander. Bows adjusted to their peak weight may draw up to four pounds heavier than the labeled max weight.

Note: It is not necessary to loosen the dowel screws to adjust the weight on any Hoyt bow. It is not necessary to lower the draw weight for storage purposes.

Note: It is normal for grease to be present on the pocket and rocker area of the bow.

CENTERSHOT ALIGNMENT

Centershot is the alignment of the arrow to the power-path of the string. The measurement from the Berger Button hole to the center of the arrow shaft should be between 1" and 5/8" for an acceptable starting point.



This is accomplished by adjusting the arrow rest left or right. This is only a starting point, fine tuning adjustments may be needed to the centershot (see **photo G**).

NOCK POINT LOCATION

Your setup and style of shooting (arrow type, fingers or release aid, arrow rest, etc.) will determine the type and location of the nocking point. A good starting point is to adjust the nock point so the arrow and string make a 90-degree angle. This is only a starting point. Fine tuning adjustments to the nocking point may be needed. Hoyt does not recommend the use of brass or other metal clamp-on nocking point devices. Only a qualified archery pro shop should install string components.

FINE TUNING

Your Genuine Hoyt Retailer is the best resource for fine tuning your bow. There are many effective methods for tuning your whole set-up. A Genuine Hoyt Retailer will be able to help you from start to finish with the entire tuning process.

TUNING FOR BROADHEADS

Most bowhunters discover that they must make slight tuning or sight adjustments when switching from practice points to broadheads (even at the same weight). Broadheads create a dramatic aerodynamic change in arrow flight. For this reason, slight adjustments may need to be made in nocking point height, rest position or bow weight to achieve desired broadhead flight. Always test shoot broadheads before hunting to ensure proper sight settings. Even expandable broadheads may require different sight settings than field points.

BOW MAINTENANCE

Your bow is a mechanical device and as such, is subject to wear and need of periodic inspection, adjustment and service. Hoyt recommends that you take your bow to a Genuine Hoyt Retailer at least once a year for a professional maintenance, cleaning and inspection. Areas to be inspected are axles, spacers, e-clips, strings, cables, limbs, cams, pockets, pocket rockers and slides, and riser. **Note:** It is normal for grease to be present on the pocket and rocker area of the bow.

STRINGS AND CABLES

Apply a light coat of bowstring wax to your bow's cables and string on a regular basis. Hoyt suggests once every two weeks during peak use. Use a high quality bowstring wax available at your local Genuine Hoyt Retailer. This will keep your bow's strings and cables in good condition. To ensure best results, replace your


string and cables when wear is evident or every two years under normal use conditions. Insist that FUSE Custom Strings and Cables be used on your bow. All Hoyt bow models come equipped with the FUSE Custom String System. Always replace your strings with FUSE brand strings. Beware of lesser quality strings and cables, as they may alter the performance of your bow or cause damage to it, possibly voiding the warranty. Never expose your string and cables to extended periods of extreme heat or prolonged moisture. Only a Genuine Hoyt Retailer should install string components. A bow should not be drawn or shot without the string components properly installed and secured. (For example: Peep sight, kissers button, nock point, D-loop, string silencers, etc.) Improper installations of string components are a potential safety hazard. Hoyt does not recommend the use of brass or other metal clamp-on nocking point devices.

LIMBSHOX AND STRING SILENCERS

Some Hoyt bows come standard with limb dampers and/or string silencers to decrease vibration and noise. Inspect them periodically and replace when wear is evident. These dampers and silencers are not covered under warranty. **Note:** Always remove LimbShox before putting the bow in a bow press.

STEALTHSHOT™ STRING SUPPRESSOR

StealthShot is a highly effective noise and vibration dampening system. For optimum performance, make sure the StealthShot's rubber damper is just touching the string at brace height (no pressure). By loosening the screw on the damper, you can rotate it so the string lies in the center.



PAINT AND FINISH

The paint and finish on your bow requires very little maintenance. A few simple actions can help keep your bow looking new. Keep it clean by removing mud, dust and other contaminants from the finish by using a damp cloth. After use during wet conditions, towel-dry your bow to prevent water damage. (Do not use a heat source to dry your bow.) Do not use chemicals, solvents or products such as bug repellents that may harm your bow's finish. Any damage to the paint and finish caused by, but not limited to, chemicals, solvents, scent sprays, or other products will not be covered under warranty. Warranty coverage of paint and finish is limited to manufacturing defects only.



CAM LUBRICATION

Bows equipped with the Cam & 1/2 Performance System feature sealed ball bearings, which do not require lubrication. For conventional bearings or bushings, such as those found on non Cam & 1/2 (dual cam) equipped bows, a light spot lubrication of the axles where they pass through the cam should be done on a regular basis (1,500 - 2,000 shots). In adverse hunting conditions where dirt, dust or moisture is encountered, lubrication may be done on a daily basis. Be sure to clean off any excess lubricant as it will attract dust and dirt and could possibly damage painted surfaces. Hoyt recommends you use a silicone or Teflon based lubrication. **It is NOT recommended that you use "Penetrating Oils" such as WD-40, EZ-#7, Fast Break, etc. as these products can damage your bow.**

COMPOUND BOW SETUP, TUNING AND MAINTENANCE (continued)

USING A BOW PRESS

⚠WARNING: To avoid severe personal injury, to yourself or bystanders, as well as damage to your bow, it is of the utmost importance that only Hoyt approved bow presses should be used to press Hoyt bows. **STANDARD BOW PRESSES CANNOT BE USED** and may result in bow failure and personal injury.


Due to the past-parallel limb angle on some models of Hoyt bows, only specific bow presses can safely be used. All Hoyt bows that feature the Hoyt UltraFlex™ Limb System, which include the Carbon Defiant, Carbon Defiant 34, Carbon Defiant Turbo, Pro Defiant, Pro Defiant 34, Pro Defiant Turbo and HyperEdge, **MUST NEVER** be pressed in standard bow presses.

Any damage caused to a Hoyt bow by a bow press not approved by Hoyt **WILL NOT** be covered under Hoyt warranty. If you are unsure if a specific bow press is suitable for use, do not press the bow and call Hoyt Customer Service at 1-801-363-2990 or visit www.hoyt.com/safetyandwarnings to learn more about Hoyt approved bow presses.

Hoyt recommends that only Genuine Hoyt Retailers press any Hoyt bow.



This style of bow press is **NOT** Hoyt approved for past parallel limb bows and should not be used on those models.



Hoyt Approved Bow Press *X Press Pro Press*


APPROVED BOW PRESSES

The following bow presses have been tested and approved by Hoyt to be used on all Hoyt model bows, including those that feature the UltraFlex Limb System (Carbon Defiant Series, Defiant Series & HyperEdge) and all other Hoyt model bows:



- » **The Last Chance EZ Press™** – **ONLY** WHEN EQUIPPED WITH THE NEW LAST CHANCE ULTRA-LOCK ADAPTERS (Last Chance UltraLock Adapters are to be used exclusively on the Last Chance EZ Press).
- » **The X Press Pro Press™**
- » **Spikepress Bow Press™**
- » **Specialty Archery Pro Press™**
- » **Synunm Archery Portable Press™**
- » **Buckeye Bow-A-Constrictor™ bow press** – **ONLY** WHEN USED WITH ULTRAFLEX ADAPTER STRAPS.
- » **The Bowforce Hunter V-Press™** with their exclusive “Limb Capture” attachment (only when the limb capture attachment is positioned correctly as shown on the right).

⚠WARNING: Failure to abide by this list of bow presses can result in personal injury to yourself or bystanders, failure of the bow, and will void the manufacturer’s warranty.



Note: Some cams, including the DFX Cam, have an optional Limb Stop Peg. If the optional Limb Stop Peg is installed on your bow, it must be removed before pressing the bow. Failure to do so could result in damage to your bow.




Last Chance EZ Press with Hoyt approved Ultra-Lock adapters.



Bowforce Hunter V-Press with Limb Capture positioned **CORRECTLY** for Hoyt bows.




Bowforce Hunter V-Press with “Limb Capture” attachment positioned **INCORRECTLY** for Hoyt bows.



ZT CABLE GUARD SYSTEM™

The ZT Cable Guard System is factory installed and requires no additional installation. The roller wheels feature sealed bearings that require no lubrication. If wax or dirt accumulate on the roller wheels, simply clean the wheels with a soft cloth.



Note: In order to remove both the split yoke buss cable and control cable from the ZT Cable Guard, the strings and cables must first be relaxed with the proper use of a bow press [see pg. 10] Once the cables are relaxed, the roller wheels and spacers can be removed by loosening and removing the shoulder bolt with a 5/32” Allen key, allowing the cables to be free.

When reassembling the unit, the roller wheels and spacers must be installed correctly. The larger side or flanged side of the bearing should face away from the bow’s shelf. One .050” spacer must be installed between the roller wheels and another one between the inner wheel and threaded mount.

When properly installed, the split yoke buss cable will route in the wheel track closest to the arrow and the control cable routes in the wheel track closest to the bow’s shelf. The cables are designed to cross at the roller wheels, but never touch one another. Install the cables into the proper wheel tracks before threading and tightening the screw to 15 in-lbs. Do not over tighten.

The ZT Cable Guard’s flexible limb assembly is maintenance free and should not be tampered with or adjusted. If the unit needs to be disassembled for cleaning purposes or installation of shock rods, loosen the button head screw with a 1/8” Allen key. The screw should be retightened to 12 in-lbs. Do not over tighten.

Do not loosen any part of the ZT Cable Guard system without first relaxing the cables by proper use of a bow press. [Pg. 10]

Do not draw or shoot the bow without the ZT Cable Guard and cables properly installed.

COMPOUND BOW SETUP, TUNING AND MAINTENANCE (continued)

PREVAIL CABLE GUARD SYSTEM

The Prevail Series bows come standard with an adjustable cable guard to optimize arrow clearance and enhance tuning. The cable guard has four different settings (0, 3, 6, and 9 degrees) and comes factory set in the 0 setting



Notice: **DO NOT** attempt to adjust or loosen the adjustable cable guard bar while the cables are still in the cable slide.



Always remove the cables from the cable slide before loosening or adjusting the cable guard bar.

Before adjusting the cable guard, first remove the cables from the cable slide. Then loosen both of the socket head cap screws 1-2 turns with a 9/64" Allen key. Rotate the bar through the series of internal notches until the desired location is obtained. Retighten the screws to 20 in-lbs, and reinstall the cable slide. Do not tighten the screws unless the positioning marks line up with the desired setting. Before drawing or shooting the bow, make sure that all parts of the arrow are getting proper clearance. The arrow or arrow fletchings should never come in contact with the cables throughout the draw cycle or shot. If any part of the arrow or fletchings come in contact with the cables, readjust the bar to a further out setting to allow for more clearance.

⚠WARNING: Do not draw or shoot bow without the cable guard, cable slide and/or rollers properly installed, adjusted and tightened.

CABLE GUARD INSTALLATION

Some Hoyt bows are designed with a standard built-in cable guard bar attachment. To install the cable guard bar, simply slide the bar through the two mounting holes on the riser, making sure the bar is pushed completely




Photo H

through and flush with the end of the front mounting hole. After the bar has been inserted, fasten with the 1/4-20 x 1/2" set screws provided. (See **photo H**) The use of Loctite® is recommended when re-inserting screws.

CABLE SLIDE INSTALLATION

To prevent your bow's cables from rubbing against each other, Hoyt uses a specially designed cable slide that has offset cableslots. To correctly install the slide on most Hoyt bows, first place the glide on the cable guard bar (see **photo I**). Next, push the control cable into the shorter front slot. Then, push the buss cable into the longer rear slot.




Photo I

DRAW LENGTH ADJUSTMENT FOR DFX, DFX TURBO AND POWERMAX CAMS

Both Top and Bottom Cam: To adjust the draw length of Hoyt's DFX, DFX Turbo & PowerMax cams with a rotating inner-cam module with draw stop pegs, use a T-20 Torx Wrench to loosen both module screws 1.5 - 2 full turns (see **Fig. A**). There is no need to completely remove either of the module screws during adjustment,




Fig. A



Fig. B

only loosen them. Once the screws are loosened, simply press the module against the surface of the cam and rotate the module (**Fig. B**) to the desired position and tighten both modules screws (Do not over tighten). Factory setting = 15 in. lbs. After adjusting the rotating inner cam modules to the same position on the top and bottom cams to achieve the desired draw length, remove the **black** draw stop from the top cam and the **red** draw stop peg from the bottom cam with a 5/64" Allen key and reinstall it in the threaded hole that corresponds with the letter on the rotating inner-cam module position, making sure to install the **black** draw stop in the top cam and the **red** draw stop peg is installed in the bottom cam. For example: E module position

should match E draw stop position. Each lettered position will provide approximately 1/2 inch of draw adjustment. The longest draw length position is E for the DFX cam and J for the PowerMax and the shortest draw length position is A.

Note: The draw stop pegs for this system are cam specific. The taller/longer, black draw stop peg is required for the top cam, while the shorter, red draw stop peg is required for the bottom cam. NEVER change either peg from its required cam.

⚠CAUTION: Use of the black draw stop peg in the bottom cam may cause the peg to hit the control cable during the draw cycle.

LIMB STOP ADJUSTMENT

DFX and DFX Turbo Limb Stop Feature: Models using the new DFX and DFX Turbo cams both come with an optional limb stop in addition to the standard cable stop pegs. Use of the limb stop peg is optional for a firmer wall at full draw. Never use the limb stop without both cable stop pegs installed.

NOTICE: Before installing the limb stop peg, first time/synchronize the cams using the draw stop pegs (black - top cam and red - bottom cam). After the cams have been properly timed, install the limb stop in the corresponding starting position that matches the module installed on the bow and draw the bow to ensure timing is correct. Additional adjustments may be needed to fine tune the desired feel when at full draw.




Fig. C

Note: The limb stop peg must be removed before pressing the bow. Failure to do so could result in damage to your bow.

The limb stop is to be used in addition to the cable draw stop pegs that come installed in the cam. Once you have adjusted the module and cable draw stop pegs to the desired positions, simply install the limb stop into the limb stop slot using a 7/64" Allen key as shown in (**Fig. C**). The alignment marks for the limb stop are a starting reference only and the limb stop may require adjustment from the starting position in order to achieve optimum feel and performance.




Fig. D

DRAW LENGTH ADJUSTMENT FOR ADJUSTABLE DRAW LENGTH BOWS (EXCEPT DFX CAMS. SEE PREVIOUS PAGE FOR DFX INSTRUCTIONS).

Follow the directions below to adjust the draw length on Hoyt bows equipped with a rotating inner-cam module such as those found on some Target bows and youth bows.

Top Cam: To adjust the draw length of Hoyt's cams with a rotating inner-cam module like the one shown in (**Fig. E**), use the appropriate wrench (some cams use an Allen key and others use a Torx wrench) to loosen the fastening screw and remove the draw length screw (see **Fig. E**). Rotating the inner-cam module in the (+) direction will lengthen the draw. Rotating the inner-cam module in the (-) direction will shorten the draw. Each lettered position will provide approximately 1/2 inch longer/shorter draw than the previous setting. Once the inner-cam module is in the desired location, reinstall and tighten the draw length screw first and then the fastening screw.

See next page for Bottom Cam adjustment procedure




Fig. E




Fig. F

HOYT
ARCHERY

Next, safely draw the bow and check the timing of the cable stop pegs relative to the limb stop. Let the bow down and make small adjustments to the limb stop position until it contacts the limb at the same time the cable stop pegs contacts the cable at full draw. (**Fig. D**)

COMPOUND BOW SETUP, TUNING AND MAINTENANCE (continued)

Note: On dual cam systems, such as those found on the Tribute and youth model bows, repeat the top cam draw length adjustment instructions on the bottom wheel as well.

Bottom Cam: Remove the draw length screw, rotate the inner-cam module to the same lettered position as the top inner-cam module, and replace the screw (see Fig. F on page 13). You must have both top and bottom inner-cam modules in the same lettered position or the bow will not tune properly. It may be necessary to use Blue Loctite® on the inner-cam module screws to keep them secure. If your cam system is equipped with an optional draw stop peg, make sure it is installed in the corresponding letter to match the module position. For example, if the module on your cam is set in the C position, make sure the draw stop peg is installed in the C position.

⚠WARNING: Never draw a bow with mismatched or missing cam modules, module screws and/or set screws. Never draw a bow with a missing or incorrectly installed draw stop peg. Never remove the cam control cable peg as serious injury and bow damage could occur.

Exchangeable Module Adjustment: Follow the directions below to adjust the draw length on a Hoyt bow equipped with an exchangeable module (SVX Cam & 1/2).

No bow press is needed to make the following adjustments. Once you have determined the desired draw length, simply loosen and remove the module screws with a standard 7/64 Allen key. There are 3 screws on the top cam and 2 screws on the bottom cam that hold the modules in position. Once the screws have been loosened and removed, simply remove the modules from the cams. Then replace the modules with ones that correspond to the desired draw length. (Do not over-tighten module screws.) It may be necessary to use blue Loctite® on the module screws to keep them secure. After the desired draw modules are installed, the draw-stop that is located on the bottom cam needs to be adjusted. Remove the draw stop with a 5/64 Allen key and reinstall it in the threaded hole that corresponds with the letter on the cam module. For example: Cam module RK-2A-BR would use draw-stop peg position A. For a detailed instructional video on cam and draw length adjustment please visit: <http://www.youtube.com/watch?v=T-51Z-z98Zc>


Draw length modules of various sizes may be purchased at your local Genuine Hoyt Retailer.

ADJUSTING YOUR BOW TO FACTORY SETTINGS

To verify that the factory specifications (cam orientation, draw length, draw weight, brace height, axle-to-axle, etc.) are correct, use a proper bowpress and remove the string and cables (this should only be done by a Genuine Hoyt Retailer). Then measure the string and cables and add or remove twists to obtain the proper length. Strings and cables must be measured under 100 lbs. of load. Then re-install the correct length string and cables. Once the string and cables are installed on the bow, only add twists to either the control cable or buss cable to synchronize the draw stops on the cams at full draw.

CAM SYNCHRONIZING

Hoyt Cam & 1/2 Performance Systems require very little maintenance. Once the shooting string, control cable and buss cable are set to the correct lengths, cam synchronizing should require little or no maintenance. Both top and bottom cams are slaved together via the control cable – forcing both cams to always move together, regardless of when the cables come into contact with the cable stops. There is a broad range where the cams can be synchronized. Hoyt Engineers and Hoyt Professional Shooters alike have found that varying the cam synchronization has little or no variation on downrange arrow impact. If you feel that the cam synchronizing or positioning is incorrect due to the shooting string, control cable or buss cable not being in specification, note the following instructions: (see **photos J and K**).



Measure your strings and adjust them to the recommended factory length by adding or subtracting twists. Then reinstall the adjusted strings onto the bow. When drawing the bow back, if the control cable-stop located on the top cam touches before the yoked buss cable-stop on the bottom cam, shorten the control cable by adding twists. When drawing the bow back, if the yoked buss cable stop on the bottom cam touches before the control cable stop on the top cam, shorten the

yoked buss cable by adding twists.

Note: Hoyt measures bowstrings using the ATA (Archery Trade Association) standard method.

X3 AND DFX CAM LET-OFF ADJUSTMENT

X3 and DFX cams are available with either 65% or 75% let-off modules. Changing the let-off should be done by Hoyt or a Genuine Hoyt Retailer. To change the let-off on the top cam: Remove the top cam module and replace it with the desired let-off module. To change the let-off on the bottom cam: Remove the bottom module and replace it with the desired let-off module. For top and bottom DFX cams, and for bottom X3 cams, 75% mods use a different draw stop peg than the 65% mods so be sure to change the draw stop peg when changing the module. Be sure the module numbers correspond with the cam numbers. For example, a X3 #2 cam would take a X3-2 mod. Be sure to adjust the modules to the same lettered module position as each other. For example, if the top module is in the "E" position, the bottom module must be in the "E" position. (Note: Blue Loctite(r) may be used to on the module screws when replacing modules to keep them from coming loose during use.)

⚠WARNING: Never draw back a bow with mismatched or missing cam modules and set screws.

BACK WALL ADJUSTMENT

X3 and SVX cams have the option to change how the back wall of the cam feels at full draw. For the X3 cam, you can remove the draw stop peg from the bottom cam to create a slightly "softer" wall at full draw. On the SVX cam, moving the peg from the outer hole to the inner hole will create a "softer" wall at full draw.

AXLE E-CLIP INSTALLATION CRITERIA



NOTE WHEN E-CLIP IS FULLY SEATED – YOU SHOULD FEEL AND HEAR IT CLICK INTO PLACE.

⚠WARNING: While servicing Hoyt compound bows, it may be necessary to remove and reinstall e-clips on the ends of the axles. It is critical that the e-clips are installed

correctly. If e-clips are not installed correctly, it is likely that one or more of the limbs will work their way off the end of the axle, causing the bow come apart and may result in injury to user or bystanders.

PREVAIL AND HYPER EDGE GRIP SYSTEM

The Prevail and Hyper Edge bow models come standard with a modular grip system. Bows come factory installed with the 0 (18 Degree Neutral/ Traditional Angle) grip module. To change the modules for a different angle, simply loosen and remove the socket head cap screws with a 7/64 Allen Key and then remove the module. Insert the desired module into the grip bed and replace the screws, tighten to 15 in-lbs. Do not over tighten.

- 0 (18 Degree Neutral/ Traditional Angle)
- +2 (20 Degree)
- +4 (22 Degree)
- +6 (24 Degree)

LOCATING YOUR SERIAL NUMBER

The six or seven-digit serial number on Hoyt compound bows is located on or near the arrow rest mount. If you have already attached a rest to your riser, you may have to remove it to see the serial number. The serial number on Hoyt Carbon bows is found between the sight mounting holes. The serial number on the PowerMax series will be found under the grip. To locate, simply remove the two attachment screws and remove the grip. The Serial number for a Prevail series bow is located under the cable guard bar.

HOYT CARBON RISER SPECIAL PRECAUTIONS AND INFORMATION:

1) **⚠WARNING:** Composite constructed components, such as Hoyt Carbon Risers, may show small surface separations in the paint and/or top surface layer of the construction. This is a typical composite condition which may become more visible as the bow is used over time. These small separations are considered normal and non-structural provided that they are under 1/8 inch in length and less than 1/32 inch wide at its widest location. These are typically not fractures or breaks in the carbon fibers themselves and do not represent a structural failure. For separations that are larger than 1/8 inch in length and/or wider than 1/32 inch wide, the bow should not be shot and should be returned to Hoyt or a Genuine Hoyt Retailer for inspection and testing. (See warranty information for instructions on returning product to Hoyt). If the bow is found to have a structural failure, the riser will be



CARBON INFORMATION AND WARRANTY

repaired or replaced under the normal conditions of Hoyt's Limited Lifetime Warranty. If the bow has no structural failure, the bow will be returned and can resume normal use.

2) ⚠️WARNING: Extreme care should be taken to avoid impact damage to a Hoyt Carbon Riser. Hoyt Carbon Risers are designed to withstand high stress flexing and high stress loading that would be associated with normal use and function of the bow. However, in general, composite structures do not withstand high load impact such as being dropped from a tree, or by having some other object impact the structure. In the event that your bow does encounter a surface impact, you must carefully inspect the riser for damage. If impacted, inspect the area for visible broken fibers, multitude of separation cracks, cracking that appears to resemble a spider-web, dented surface, or a soft flexible surface at the impact point. If any of the above conditions are apparent or suspected, the bow should be considered damaged and should not be drawn or used any further. In the event that the bow was exposed to an impact and damage is evident as described above, you can return the bow to Hoyt for an evaluation. (See warranty information for instructions on returning product to Hoyt). If the riser is determined to be damaged and not fit for use, Hoyt may offer a replacement of damaged components at the owner's expense. Damage, including impact damage, caused accidentally, whether from misuse of the product, or from use not associated with normal archery practices, is NOT covered under the Hoyt Limited Lifetime warranty.

3) Hoyt Carbon Risers, or any other component of any Hoyt bow, should not be modified in any way.

⚠️WARNING: Never mechanically alter or modify your bow as it will likely cause the bow to break. Drilling holes, cutting, filing, or sanding are examples of mechanically altering your bow.

Any modification to any bow or component will immediately void any and all warranty for the bow and/or component.

4) ⚠️WARNING: Hoyt Carbon Risers are constructed by various aluminum components that are either attached by adhesive or by mechanical fasteners such as screws to the exterior of the riser. Any attempt to remove any of the aluminum



Carbon Riser

factory attached components will damage the bow and could possibly cause harm or injury to the owner or bystanders and will immediately void any and all warranty for the bow and/or components. Do not attempt to remove or adjust the security screws attaching the stabilizer mount or the sight/arrow rest mounting insert.

5) ⚠️WARNING: Care should be given to not expose Hoyt Carbon Riser equipped bows to any solvents, lubricants, or other substances that contain silicone as the structure could be weakened. A weakened riser has the potential to cause injury to or damage other components.

6) Care should be given to not expose Hoyt Carbon Riser equipped bows to extreme heat, flame, or other adverse conditions that could possibly damage the bow.

7) Composite constructed components, such as a Hoyt Carbon Riser bows may exhibit a creaking sound during the first few shots when the bow is new. This creaking sound could come and go for the first few 100 shots. This is a normal condition for Composite structures and is not a structural failure.

If a Hoyt Carbon Riser bow has been stored for a prolonged period of time without being used (several weeks at a time), the bow may exhibit creaking sound again for the first few shots. This is a normal condition for composite structures and is not a structural failure.

LIMITED LIFETIME WARRANTY

PLEASE READ THIS DOCUMENT CAREFULLY. IT CONTAINS VERY IMPORTANT INFORMATION ABOUT YOUR RIGHTS AND OBLIGATIONS, AS WELL AS LIMITATIONS AND EXCLUSIONS THAT MAY APPLY TO YOU. Hoyt warrants to the **ORIGINAL OWNER** that the Hoyt compound bow riser, limbs, limb pockets and eccentrics will be free from defects in materials and workmanship for the lifetime of the product under the following terms and conditions:

1) Hoyt bows must be purchased from a Genuine Hoyt Retailer (**no exceptions**).

2) The original owner must retain and provide an original and dated proof of purchase (sales receipt) from a Genuine Hoyt Retailer. Hoyt bows purchased via mail order, through an unauthorized retailer, or over the Internet voids all warranty.

3) THE ORIGINAL OWNER MUST REGISTER THE BOW WITH HOYT WITHIN 30 DAYS OF PURCHASE. To register your bow, visit www.hoyt.com/customer_service/ to

complete the registration process electronically, or contact Hoyt at (801) 363-2990 to request a registration card.

4) All compound bows must have the original serial number factory-attached to the bow. The serial number must remain legible. THIS LIMITED LIFETIME WARRANTY IS NOT TRANSFERABLE.

Exclusions from Warranty Coverage:

This Limited Lifetime Warranty covers normal use of the product, and Hoyt does not warrant and is not responsible for:

1. The use of aftermarket products/accessories that alter Hoyt's specs or design.
2. Damage to strings, cables, bearings, damping materials, finish (including paint, anodize, powder coat and film-dipped finishes) resulting from normal wear-and-tear.
3. If bow shows sign of misuse, alteration, or mishandling, this warranty will be void.
4. Use of arrows weighing less than 5 grains per pound of draw weight will void the warranty.
5. Damage to 'other' accessories.
6. Aftermarket replacement strings.
7. Any modification to any bow or component.
8. Bows returned to Hoyt without a Return Authorization number obtained by a Genuine Hoyt Retailer.

OBTAINING WARRANTY SERVICE

To obtain warranty service, you must return your bow to a Genuine Hoyt Retailer. The retailer can help to determine if Hoyt factory service is required or if the retailer can complete the repair. Genuine Hoyt Retailers may provide additional services and apply additional charges for service work performed by the retailer. If the bow must be returned to the factory, **THE BOW OWNER IS RESPONSIBLE FOR THE FREIGHT CHARGES TO HOYT.** Hoyt, in turn, will pay for the same return freight of the repaired product.

Before any bow is returned to Hoyt, a Return Authorization (RA) number must be obtained through a Genuine Hoyt Retailer. Please note that Hoyt will not issue RAs to consumers. Bows returned to the factory without a Return Authorization number obtained from a Genuine Hoyt Retailer may be denied warranty service. If Hoyt determines, in its sole discretion, that a bow qualifies for warranty repair, Hoyt will make every effort to repair the bow. Repairs may be performed with original parts when available. Hoyt reserves the right to make part substitutions on warranty



coverage for any reason. If original parts are not available, suitable replacement parts/components may be used. If the Hoyt bow is not repairable, but qualifies for warranty coverage, Hoyt will replace the bow with a bow of similar feature and product class in Hoyt's sole determination.

THERE ARE NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, THAT EXTEND BEYOND THOSE WRITTEN HERE. NO AGENT, EMPLOYEE OR REPRESENTATIVE OF HOYT OR ITS RETAILERS HAVE THE AUTHORITY TO BIND HOYT TO ANY AGREEMENT NOT HEREIN STATED.

LIMITATION OF LIABILITY

IN NO EVENT SHALL HOYT BE LIABLE UNDER ANY CIRCUMSTANCE TO YOU OR ANY OTHER PARTY FOR ANY SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE PRODUCTS, EVEN IF THE COMPANY OR ANY OF THE COMPANY AFFILIATES HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. IN NO EVENT SHALL HOYT OR ANY HOYT AFFILIATE BE LIABLE TO YOU OR ANY OTHER PARTY FOR LOSS, DAMAGE, OR INJURY OF ANY KIND BEYOND THE BOW ITSELF.

This warranty gives you specific legal rights. You may also have other rights which may vary in states or countries.

Thank you for taking the time to read and understand the contents of this manual to ensure proper care and safe use of your new Hoyt bow. We are excited and grateful to have you as a part of Team Hoyt. Now, go enjoy your new bow! Get Serious. Get Hoyt.



GET SERIOUS. GET HOYT.