

2-Stages 5 HP 80 Gallon Air Compressor

Product Features:

- Powerful 5 HP running motor and magnetic starter
- 2 cylinder cast iron 2-stage oil lubricated pump
- 200 PSI max pressure for optimum tool performance
- 80 Gallon ASME registered tank provides longer run times
- ASME safety valve
- Large intake "Auto-drop" aluminum filter
- Heavy-duty 1/2" ball valve and easy to read tank pressure gauge
- Pump with "V" style design minimizes vibrations, improves cooling and extends compressor life



MODEL	KC-5280V3-MS
MOTOR	5 HP
FACTORY PRESSURE SETTINGS	95-175 PSI
MAXIMUM PRESSURE	200 PSI
AIR DELIVERY @ 175 PSI	19 CFM
TANK SIZE	80 Gallon
MOTOR AMPERAGE	25.6 Amp.
RPM	1,750
VOLTAGE	208-230V, 1 Phase, 60 Hz
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	39" x 27" x 71" / 490 lbs
PACKAGE DIMENSIONS (LxWxH) / WEIGHT	40" x 30" x 73" / 530 lbs
UPC	7 72995 02114 7

Specifications subject to change.