

2-Stage 7.5 HP 80 Gallon Air Compressor

Product Features:

- Powerful 7.5 running HP motor and magnetic starter
- 2 cylinder cast iron 2-stage oil lubricated pump
- 200 PSI max pressure for optimum tool performance
- 80 Gallon ASME registered tank provides longer run times
- ASME safety valve
- Large intake "Auto-drop" aluminum filter
- Heavy-duty 1/2" ball valve and easy to read tank pressure gauge
- Pump with "V" style design minimizes vibrations, improves cooling and extends compressor life



MODEL	KC-7280V3-MS
MOTOR	7.5 HP
FACTORY PRESSURE SETTINGS	95-175 PSI
MAXIMUM PRESSURE	200 PSI
AIR DELIVERY @ 175 PSI	24 CFM
TANK SIZE	80 Gallon
MOTOR AMPERAGE	35.5 Amp.
RPM	1,760
VOLTAGE	208-230V, 1 Phase, 60 Hz
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	39" x 27" x 70-1/4" / 520 lbs
PACKAGE DIMENSIONS (LxWxH) / WEIGHT	40" x 30" x 73" / 560 lbs
UPC	7 72995 02115 4

Specifications subject to change.