

6-1/2" Variable Speed Plunge Cut Track Saw

Product Features:

- Plunge Cut Track Saw is ideal for smooth cutting of solid wood and plywood, especially when combined with the optional 50" track model KW-300
- Powerful 12 Amp. 120V variable speed "soft-start" motor with "constant torque" technology
- Depth stop feature for splinter-free cuts
- Safety features include fully enclosed blade and anti-kickback control (when used with optional 50" track)
- Flat blade housing design allows wall cuts at 11/16" from the wall
- Mode selector enables fast and easy setting of major functions, such as blade removal, free plunge cutting and scribe/scoring cut at 0.1" deep
- Comes with efficient 1L dust management system, dust bag, dust chute, set of carbon brushes and hex. key with on cord storage



* This Plunge Cut Track Saw accepts Makita®, Dewalt®, Kreg® or Festool® 6-1/2" x 20 mm arbor blades.

* Optional track (KW-300) is compatible with Makita® and Dewalt Track Saws.

Makita® is a registered trademark of the Makita Corporation.

Dewalt® is a registered trademark of the Stanley Black & Decker Inc.

Kreg® is a registered trademark of Kreg Enterprises Inc.

Festool® is a registered trademark of the TTS Tooltechnic Systems AG & Co. KG.

MODEL	KC-8365
BLADE DIAMETER	6-1/2"
BLADE ARBOR / BLADE THICKNESS	20mm / 2.2mm
CUT CAPACITY @ 90° (WITHOUT TRACK/WITH)	2-5/16" / 2-1/8"
CUT CAPACITY @ 45° (WITHOUT TRACK/WITH)	1-21/32" / 1-1/2"
BEVEL ANGLE CAPACITY	0° to 48°
VARIABLE SPEED RANGE	2,000 - 6,000 RPM
MOTOR	12 Amp.
VOLTAGE	120V, 1 phase, 60 Hz
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	23" x 9" x 9-5/8" / 12 lbs
PACKAGING DIMENSIONS (LxWxH) / WEIGHT	13-1/4" x 10-1/8" x 11-5/8" / 14 lbs
UPC	7 72995 01729 4

Specifications subject to change.