

Forced Air Construction Propane Heater 95,000 -125,000 BTU/H

Product Features:

- Forced air heater is ideal for spaces up to 3,125 sq. feet, spaces such as construction sites, garages, workshops, warehouses and barns
- Variable heat settings for efficient use
- Continuous electronic ignition
- Safety features include high temperature limit shut-off, flame-out fuel cut and a thermocouple
- Torpedo heater design
- CSA certified for use with 20 lbs propane cylinder
- Comes with 10 ft. propane hose and regulator



MODEL	KPH-125
BTU/H	95K, 110K, 125K
FUEL CONSUMPTION (LBS/H)	4.4 / 5.1 / 5.8
MAX. OPERATING HOURS (20 LBS)	4.6
FUEL TYPE	Propane
HEATING AREA (SQ. FEET)	3,125
AIR FLOW (CFM)	400
MAX. OUTLET TEMPERATURE	260°C
MOTOR	0.8 Amp.
VOLTAGE	120V, 1 phase, 60 Hz
ASSEMBLED DIMENSIONS (LXWXH) / WEIGHT	25" x 9-1/4" x 18-1/2" / 20 lbs
PACKAGE DIMENSIONS (LXWXH) / WEIGHT	32-1/4" x 11-1/4" x 19-7/8" / 25 lbs
UPC	7 72995 02215 1

Specifications subject to change.