

Forced Air Construction Propane Heater 40,000 - 60,000 BTU/H

Product Features:

- Forced air heater is ideal for spaces up to 1,500 sq. feet, spaces such as construction sites, garages, workshops, warehouses and barns
- Variable heat settings for efficient use
- Continuous electronic ignition
- Safety features include high temperature limit shut-off, flame-out fuel cut and a thermocouple
- Torpedo heater design
- CSA certified for use with 20 lbs propane cylinder
- Comes with 10 ft. propane hose and regulator



MODEL	KPH-60
BTU/H	40K, 50K, 60K
FUEL CONSUMPTION (LBS/H)	1.9 / 2.3 / 2.8
MAX. OPERATING HOURS (20 LBS)	10.5
FUEL TYPE	Propane
HEATING AREA (SQ. FEET)	1,500
AIR FLOW (CFM)	300
MAX. OUTLET TEMPERATURE	255°C
MOTOR	0.6 Amp.
VOLTAGE	120V, 1 phase, 60 Hz
ASSEMBLED DIMENSIONS (LXWXH) / WEIGHT	18-1/4" x 7-3/4" x 15" / 14 lbs
PACKAGE DIMENSIONS (LXWXH) / WEIGHT	24-5/8" x 9-5/8" x 14-1/2" / 19 lbs
UPC	7 72995 02214 4

Specifications subject to change.