



SLX[®] **1x MICROPRISM™ T**

OPTIC MANUAL

THANK YOU FOR CHOOSING THIS PRIMARY ARMS OPTIC

If you have any questions about your new optic or any of our other products, visit us at www.primaryarmsoptics.com, email us at info@primaryarmsoptics.com, or give us a call toll-free at 855-774-2767. The customer service team at our headquarters in Houston, Texas will respond promptly.

If you have any problems with a Primary Arms Optics product, we urge you to contact us immediately and let our customer service professionals handle the situation for you. There is no need to return your optic to the retailer.


*View back cover for lifetime warranty information.

SLX® 1X MICROPRISM™_T

The SLx 1x MicroPrism_T scope is an astigmatism-friendly alternative to conventional red dot sights, providing fast target acquisition with an etched prismatic reticle. Like reflex optics, the SLx 1x MicroPrism_T is fast in close quarters, with eye relief extending from 2" all the way out to 7".

The SLx 1x MicroPrism_T is compatible with standard micro dot mounts, meaning you can easily swap the SLx 1x MicroPrism_T with most any aftermarket dot mount. Two mounts (a low mount and 2.26" mount) are included with this optic.

OPTIC FEATURES



AUTOLIVE®

Our motion-sense technology, AutoLive, greatly extends your battery life when storing optics with active illumination.



DAYLIGHT BRIGHT®

Distinguished by powerful illumination, our Daylight Bright reticles are strikingly bright, even in intense daylight conditions.



MULTI-COATED LENS

Our Multi-Coated Lenses are treated with a special finish to reduce reflections and increase light transmission.



***RED DOT BRIGHT®**

This badge is reserved for scopes with the brightest reticle illumination, comparable to the highest settings on a red dot sight.

**Available only on the T-Dot version.*



SHOCKPROOF

Our Shockproof optics are reinforced against impact, capable of facing the rigors of duty use.



WATERPROOF

Our Waterproof optics are sealed for reliable function, even when fully submerged in water.



**SCAN TO SEE MORE
PRIMARY ARMS OPTICS
FEATURES**

HOW TO SET RETICLE ILLUMINATION

Your reticle comes with a total of 13 red-illuminated brightness settings, three of which are night vision compatible. The night vision settings are unable to be seen by the naked eye and can only be viewed through a separate night vision device. The indicator triangle makes it easy to determine your brightness setting.

The illumination knob can be turned infinitely in either direction, ensuring the shortest path to your desired illumination regardless of the current illumination setting. To turn illumination off, simply return the dial to the off (0) position.

HOW TO ACHIEVE A CLEAR RETICLE PICTURE

Setting the diopter ring at the rear of the eyepiece is the critical first step to successful precision shooting. Looking at a featureless light background like a clear blue sky or blank wall, the reticle should appear sharp and crisp. If it does not, you need to

make adjustments by turning the ring. Look at the scope with quick glances and adjust until the reticle is clear at first glance. This is a one-time adjustment. Because everyone's eyes are different, the correct position will vary from person to person.

ZEROING

The optic is delivered in a centered position. Normally, this means that only small adjustments are necessary, providing that the base is properly aligned. Work your way to “zero” by adjusting each turret only a few clicks at a time. To adjust windage and elevation turn them as follows:

- a. To move the point of impact to the right, turn the windage adjustment screw counterclockwise.
- b. To move the point of impact to the left, turn the windage adjustment screw clockwise.
- c. To move the point of impact up, turn the elevation adjustment screw counterclockwise.
- d. To move the point of impact down, turn the elevation adjustment screw clockwise.

Every click will shift the position of the reticle by 1 MOA. The maximum total adjustment range for both windage and elevation is 120 MOA. If you suddenly encounter resistance, do NOT try to force the screw further, this can break the mechanism and render the sight unable to zero. Confirm zero by firing at least three shots at a zeroing target. After initial firing, check that the optic and mount are secure on your firearm. Check your impact points on the target to confirm accuracy and repeat until you are satisfied that the point of aim and the point of impact coincide at your desired range.

MOUNTING OPTIONS

The SLx 1x MicroPrism[™] includes two different mounting options: 0.96" (Low) and a 2.26" (High). The former is ideal for carbines and shotguns with lower stock combs, while the latter is best for AR-style carbines. Start by connecting the mount to the bottom of the optic. Apply a small amount of blue threadlocker, and torque the screws down to 15-20 in-lbs.

A black security type screw is also located on the underside of the optic, this is the nitrogen gas purge port. Do not attempt to adjust that screw, or the nitrogen may vent from inside the optic, compromising function. For the same reason, do not attempt to adjust the spring cover also located under the optic on the left side.

The crossbolt located on the removable base uses a T25 Torx and should be tightened to 55-60 in-lbs. applying blue thread locker to the crossbolt threads.

BATTERY COMPARTMENT

The SLx 1x MicroPrism[™] uses a single CR 2032 battery. The battery cap is located on the left side and unscrews counterclockwise using a quarter or other coin. The

positive (+) side of the battery faces out towards the cap. Rechargeable batteries are not recommended and can potentially damage the electronics.

SLX 1X MICROPRISM[†] SCOPE SPECIFICATIONS

Magnification: 1x	Click Value: 1 MOA	Total Elevation Adjustment: 120 MOA
Objective Lens Diameter: 17 mm	Field of View: 76.5 feet @ 100 yards*	Total Windage Adjustment: 120 MOA
Eye Relief: 3.6" (Usable Range: 2" to 7")	Weight (with Battery, w/o Lens Covers): 5.5 oz	Lifetime Warranty
Exit Pupil: 15.6mm	Length (w/o Lens Covers): 2.48"	Battery: 3v CR 2032

Specifications may vary and are subject to change without notice.

*Optimum FOV with 3.6 in. Eye Relief

FEATURES

- Illuminated Reticles with Target Ranging, available in Red and Green.
- Thirteen Brightness Settings (NV-Compatible to Daylight Bright).
- AutoLive motion-sensing illumination technology.
- Aluminum Alloy Main Body with Hard Coat Anodizing.
- Includes 0.96" and 2.26" Centerline Mounts.
- Compatible with Anti-Reflection Devices (ARD) (Sold Separately).
- Fully Nitrogen Purged, IP67 Waterproof, and Dust Proof
- Backed by Our Lifetime Warranty.

LENS CARE

Please do not use any organic solvent such as alcohol or acetone on your optic. First, blow dust or any foreign objects off of the lens. Then, use a soft cotton or microfiber lens cloth to clean any

fingerprints or smears off the lens. Alternatively, you may use a piece of professional lens paper for further cleaning, if necessary.

REMEMBER: THE FOUR RULES OF FIREARMS SAFETY

- Treat every firearm as if it were loaded.
- Never let your muzzle cover anything you are not willing to destroy.
- Keep your finger off the trigger until your sights are on target.
- Be sure of your target and what is behind it.

 **WARNING:** Always ensure your firearm is unloaded (chamber empty and magazine removed) before installing optics or accessories.

 **WARNING:** Improper installation of firearm parts or accessories may result in death or serious personal injury. If you are not properly trained in the installation of these parts, have them installed by a gunsmith or armorer.

 **WARNING:** This product can expose you to chemicals including Nickel (Metallic), a carcinogen, and Lead, a reproductive toxicant. See www.P65Warnings.ca.gov

WARNING

- **INGESTION HAZARD:** This product contains a button cell or coin battery.
- **DEATH** or serious injury can occur if ingested.
- A swallowed button cell or coin battery can cause **INTERNAL CHEMICAL BURNS** in as little as **2 HOURS**.
- **KEEP** new and used batteries **OUT OF REACH OF CHILDREN**.
- **SEEK IMMEDIATE MEDICAL ATTENTION** if a battery is suspected to be swallowed or inserted inside any part of the body.



- Remove and immediately recycle or dispose of used batteries according to local regulations and keep away from children. Do NOT dispose of batteries in household trash or incinerate.
- Even used batteries may cause severe injury or death.
- Call a local poison control center for treatment information.
- Non-rechargeable batteries are not to be recharged.
- Do not force discharge, recharge, disassemble, heat above (manufacturer's specified temperature rating) or incinerate. Doing so may result in injury due to venting, leakage or explosion resulting in chemical burns.
- Ensure the batteries are installed correctly according to polarity (+ and -).
- Do not mix old and new batteries, different brands or types of batteries, such as alkaline, carbon-zinc, or rechargeable batteries. Remove and immediately recycle or dispose of batteries from equipment not used for an extended period of time according to local regulations.
- Always completely secure the battery compartment. If the battery compartment does not close securely, stop using the product, remove the batteries, and keep them away from children.



LIFETIME WARRANTY

Your Primary Arms SLx® 1x MicroPrism™† Optic is covered by the Primary Arms Lifetime Warranty. If a defect due to materials or workmanship, or even normal wear and tear has caused your product to malfunction, Primary Arms will either repair or replace your product. You can find more details about our lifetime warranty at www.primaryarmsoptics.com. *See warranty card for details.

Email: info@primaryarmsoptics.com

Toll-free at 855-774-2767

www.primaryarmsoptics.com



SCAN HERE for
more information
on these optics.

©Copyright 2025 PRIMARY ARMS, LLC
is a registered trademark of PRIMARY ARMS, LLC

For Patent Information go to primaryarmsoptics.com/patents