Fuel EX

Model	Fuel EX 5.5 & 6.5		Fuel EX 7, 8. 9 (Fox RP2)		Fuel EX 9.0, 9.5 (Fox RP23)		
Travel (mm)	120		120		120		
Stroke (mm)	50		50		50		
Sag (%)	25		25		25		
Sag (mm)	12		12		12		
Rider (lbs/kg)	Spring (psi)	Rebound	Spring (psi)	Rebound	Spring (psi)	Rebound	Platform Number Setting
100/45	50	6 clicks out from slow	50	7 clicks out from slow	50	7 clicks out from slow	Start in #2 Position. Adjust per desired efficiency (3 for more platform, 1 for more active)
110/50	60		60		60		
120/55	70		70		70		
130/59	80		80		80		
140/63	90		90		90		
150/68	100		100	5 clicks out from slow	100	5 clicks out from slow	
160/73	110		110		110		
170/77	120		120		120		
180/82	130		130		130		
190/86	135		135		135		
200/90	145		145		145		
210/95	160		160	3 clicks out from slow	160	3 clicks out from slow	
220/100	165		165		165		
230/104	175		175		175		
240/109	185		185		185		
250/113	195		195		195		
Notes	* Sag measurements must be made with ProPedal lever in OPEN position						

Suspension Setup

1.) Determine rider weight
2.) Apply initial pressure and settings
3.) Mount bike and then settle into riding position
4.) Move O-ring up to shock dust seal
5.) Dismount
6.) Measure distance from O-ring to dust seal
7.) Adjust pressure until measurement matches suggested sag
8.) Test ride and adjust according to feedback

TREK