Top Fuel

| | Top Fuel | | | | |
|---|---|---|---|---|---|
| Model | Top Fuel 7, 8 & 69er (Fox RP2) | | Top Fuel 9.8 and 9.9 SSL (Fox RP23) | | |
| Travel (mm) | 90 | | 90 | | |
| Stroke (mm) | 38 | | 38 | | |
| Sag (%) | 25 | | 25 | | |
| Sag (mm) | 10 | | 10 | | |
| Rider (lbs/kg) | Spring (psi) | Rebound | Spring (psi) | Rebound | Platform Number Setting |
| 100/45 | 75 | 7 clicks out from slow | 75 | 7 clicks out from slow | Start in #2 Position. Adjust per desired efficiency (3 for more platform, 1 for more active) |
| 110/50 | 85 | | 85 | | |
| 120/55 | 90 | | 90 | | |
| 130/59 | 95 | | 95 | | |
| 140/63 | 100 | | 100 | | |
| 150/68 | 105 | 5 clicks out from slow | 105 | 5 clicks out from slow | |
| 160/73 | 110 | | 110 | | |
| 170/77 | 120 | | 120 | | |
| 180/82 | 135 | | 135 | | |
| 190/86 | 150 | | 150 | | |
| 200/90 | 160 | | 160 | | |
| 210/95 | 165 | 3 clicks out from slow | 165 | 3 clicks out from slow | |
| 220/100 | 170 | | 170 | | |
| 230/104 | 175 | | 175 | | |
| 240/109 | 185 | | 185 | | |
| 250/113 | 190 | | 190 | | |
| Notes | * Sag measurements must be made with RP lever in OPEN position | | | | |

**Suspension Setup**

1.) Determine rider weight
2.) Apply initial pressure and settings
3.) Mount bike and then settle into riding position
4.) Move O-ring up to shock dust seal
5.) Dismount
6.) Measure distance from O-ring to dust seal
7.) Adjust pressure until measurement matches suggested sag
8.) Test ride and adjust according to feedback

TREK