

YEAR 2019 SPEEDPLAY ROAD SHOE COMPATIBILITY GUIDE**

ZERO, ZERO AERO, ZERO PAVÉ, ULTRA LIGHT ACTION OR LIGHT ACTION PEDALS WITH WALKABLE CLEATS

WARNING! - Use only Walkable Cleat Fastening Screws supplied with Zero Aero or Ultra Light Action Walkable Cleats. Do NOT use previous versions of Cleat Fastening Screws with the Zero Aero or Ultra Light Action Walkable Cleats. All previous versions of Cleat Fastening Screws are not compatible with Zero Aero or Ultra Light Action Walkable Cleats and can affect the engagement and retention of the pedal system which can lead to a fall that can result in severe injury. **Never install cleats using any combination of new cleat parts and old cleat parts.** When replacing cleats, replace **all** used parts with Walkable Cleat parts.

NOTE: VARIATIONS IN SHOE SOLE CURVATURES MAY REQUIRE SNAP SHIMS OTHER THAN THOSE RECOMMENDED BELOW. PLEASE VISIT OUR WEBSITE AT WWW.SPEEDPLAY.COM TO SEE OUR CLEAT INSTALLATION VIDEO UNDER TECH SUPPORT / VIDEO LIBRARY.

2019 MODEL SHOES COMPATIBLE WITH FACTORY-INSTALLED 5-F AND 5-R SNAP SHIMS

Bont 3 hole // Bontrager Nylon // Bontrager Silver Series Carbon // Crono CR - 1 CR - 3 // Exustar // FLR // Lake
Mavic // Nalini Carbon // Scott Nylon // Spiuk Carbon // Suplest

SNAP SHIMS REQUIRED FOR NON-STANDARD 2019 MODEL SHOES AND PRIOR YEAR MODEL SHOES

Bont - All	Current year & earlier	Use 5-F & 5-R Snap-Shims. May require "Extra Shim" under cleat-mounting screw of each V.2 Base Plate.
Bontrager - Carbon - All	Current year & earlier	* Remove 5-F & 5-R Snap-Shims. Install 6-F & 6-R Snap-Shims. May require "Extra Shim" under cleat-mounting screw of each V.2 Base Plate.
Crono - CR - 1 & CR - 3	2019 & earlier	Use 5-F & 5-R Snap-Shims.
Crono - CR - 2	2019 & earlier	* Remove 5-F & 5-R Snap Shims. Install 6-F & 6-R Snap Shims.
Diadora - Nylon, Carbon, Votex Pro	Current year & earlier	* Remove 5-F & 5-R Snap-Shims. Install 6-F & 6-R Snap-Shims. May require "Extra Shim" under cleat-mounting screw of each V.2 Base Plate.
DMT - All	Current year & earlier	* Remove 5-F & 5-R Snap-Shims. Install 6-F & 6-R Snap-Shims. May require "Extra Shim" under cleat-mounting screw of each V.2 Base Plate.
Exustar - All	Current year & earlier	Use 5-F & 5-R Snap-Shims. May require "Extra Shim" under cleat-mounting screw of each V.2 Base Plate.
Fizik - All	Current year & earlier	* Remove 5-F & 5-R Snap-Shims. Install 6-F & 6-R Snap-Shims. May require "Extra Shim" under cleat-mounting screw of each V.2 Base Plate.
Gaerne - All	Current year & earlier	* Remove 5-F & 5-R Snap Shims. Install 6-F & 6-R Snap Shims. May require "Extra Shim" under cleat-mounting screw of each V.2 Base Plate.
Giant	Current year & earlier	* Remove 5-F & 5-R Snap Shims. Install 6-F & 6-R Snap Shims. May require "Extra Shim" under cleat-mounting screw of each V.2 Base Plate.
Giro - All Carbon & Nylon	2012 - 2019	* Remove 5-F & 5-R Snap Shims. Install 6-F & 6-R Snap Shims.
Lake - All Carbon & Nylon	2011 & earlier	* Remove 5-F & 5-R Snap Shims. Install 6-F & 6-R Snap Shims.
Lake - All Carbon & Nylon	2019 & earlier	Use 5-F & 5-R Snap-Shims.
Louis Garneau - All	Current year & earlier	* Remove 5-F & 5-R Snap Shims. Install 6-F & 6-R Snap Shims. May require "Extra Shim" under cleat-mounting screw of each V.2 Base Plate.
Louis Garneau Carbon Ergo	Current year & earlier	Use 5-F & 5-R Snap-Shims. May require "Extra Shim" under cleat-mounting screw of each V.2 Base Plate.
Mavic	2019 & earlier	Use 5-F & 5-R Snap-Shims.
Nalini Carbon	2009 - 2019	Use 5-F & 5-R Snap-Shims.
Northwave Speedplay	Current year & earlier	Omit V.2 Base Plate. Requires Northwave-supplied kit: NW Speedplay adaptor (Available through Northwave).
Northwave Centurion, Mirage, Solo, Diana Road, Husky	Current year & earlier	Omit V.2 Base Plate. Use Northwave-supplied Time/Speedplay insert. Requires 4x9.5mm Walkable Cleat Fastening Screws (Part #14145) available from Speedplay.
Pearl Izumi - All	2012 - 2019	* Remove 5-F & 5-R Snap Shims. Install 6-F & 6-R Snap Shims.
Pearl Izumi	2011	Use 5-F & 5-R Snap-Shims.
Scott - All Carbon & Nylon	2019 & earlier	* Remove 5-F & 5-R Snap Shims. Install 6-F & 6-R Snap Shims.
Serfas - Carbon	2013 - through - 2016	* Remove 5-F & 5-R Snap Shims. Install 6-F & 6-R Snap Shims. May require "Extra Shim" under cleat-mounting screw of each V.2 Base Plate.
Shimano - All	2019 & earlier	* Remove 5-F & 5-R Snap Shims. Install 6-F & 6-R Snap Shims.
Sidi - All	2019 & earlier	* Remove 5-F & 5-R Snap Shims. Install 6-F & 6-R Snap Shims.
Sidi - Carbon Lite & Glass Fiber Comp	2012	Use 5-F & 5-R Snap-Shims.
Specialized - All	2010 - 2019	* Remove 5-F & 5-R Snap-Shims. Install 6-F & 6-R Snap-Shims.
Spiuk - Carbon	2019 & earlier	Use 5-F & 5-R Snap-Shims.
Spiuk - Glass Fibre	2019 & earlier	* Remove 5-F & 5-R Snap Shims. Install 6-F & 6-R Snap Shims.
Time	2009 - through - 2012	* Remove 5-F & 5-R Snap Shims. Install 6-F & 6-R Snap-Shims. May require "Extra Shim" under cleat-mounting screw of each V.2 Base Plate.
Vittoria - All	2011 - 2019	* Remove 5-F & 5-R Snap Shims. Install 6-F & 6-R Snap Shims.
Xpedo	2012 & earlier	* Remove 5-F & 5-R Snap Shims. Install 6-F & 6-R Snap-Shims.

*** Ensure the factory-installed cleat nuts remain in the V.2 Base Plate.**

Shoes with 4-hole cleat pattern (Speedplay V.2 Base Plate not used).

Bont / DMT / Lake / Rocket 7 / Sidi / Vittoria / Gaerne / Riivo / Pinnacle Racing	Current year & earlier	Omit V.2 Base Plate. See note below regarding 4-Hole Carbon Fiber Soles.
---	------------------------	--

For Shoes and Years not listed, Please call Speedplay for assistance.

4-Hole Shoe Soles: Must use the Walkable Cleat Protector Shim Kit (Part #14135), sold separately and available from Speedplay, to prevent contact between the pedal body and the shoe sole. If the Walkable Cleat Protector Shim Kit is not used, serious wear damage to the shoe sole and the cleat will result.

WARNING! - Do not use the Snap-Shim Cleat mounting screws with any previous models of Speedplay X cleats including the Slim Line Cleat. The Snap-Shim Cleat mounting screw heads are too small and may pull through the older base plates. This may cause the cleat to pull off the shoe causing a fall that may result in severe injury.

**** See detailed photos of select sole mountings and the latest updates for shoe compatibility at www.speedplay.com or call the Speedplay Tech Department at 1-800-468-6694 (PST).**