



Undercounter Dishwasher

PRODUCT MODEL NUMBERS

DU640XTK	GU1200XTL
DUL300XTK	GU1200XTK
DUL300XTL	GU1500XTL
GU1100XTL	GU1500XTK
GU1101XTL	GU630XTL
GU1108XTL	GU640XTL

Electrical: 120-volt, 60-Hz, AC-only, 15- or 20-amp. electrical supply. Use copper wire only. A time-delay fuse or circuit breaker and separate circuit is recommended.


Water: A hot water line with 20-120 psi (138-862 kPa) water pressure. Water temperature must be 120°F (49°C) at dishwasher. Use 3/8" O.D. copper tubing with compression fitting or flexible stainless steel braided fill line (1/2" minimum plastic tubing is optional but not recommended). Use a 90° elbow with 3/8" N.P.T. external pipe threads on one end to connect to water inlet valve. Do not solder within 6" (15.2 cm) from water inlet valve.

Drain: Use the new drain hose supplied with your dishwasher. If this is not suitable, use a new drain hose with a maximum length of 12 feet (3.7 m) that meets all current AHAM/IAPMO test standards, is resistant to heat and detergent, and fits the drain connector of the dishwasher. Must have a high drain loop 20 inches (50.8 cm) above the subfloor or floor. Connect drain hose to waste tee or disposer inlet above drain trap in house plumbing and 20 inches (50.8 cm) minimum above the floor. An air gap must be used if the drain hose is connected to house plumbing lower than 20 inches (50.8 cm) above subfloor or floor. Use 1/2" minimum I.D. drain line fittings.


Grommet is required for electrical cable or power supply cord hole cut in a metal cabinet.

Do NOT install dishwasher over carpeted floor.

OVERALL DIMENSIONS



CABINET OPENING DIMENSIONS



*Measured from the lowest point on the underside of countertop. May be reduced to 33-7/8" (86 cm) by removing wheels from dishwasher.

**Minimum, measured from narrowest point of opening.

***Maybe increased to 6-7/8" (17,5 cm) if height of opening is 34-1/2" (87,6 cm) at lowest point.

†Both sides