



Microwave Hood Combination


PRODUCT MODEL NUMBERS

GMH3174XV	GMH6185XV	MH2175XS	WMH1164XW
GMH3204XV	MH1160XS	WMH1162XV	WMH2175XV
GMH5184XV	MH1170XS	WMH1163XV	WMH2205XV
GMH5205XV	MH1171XV	WMH1164XV	WMH3205XV

Electrical: A 120-Volt, 60-Hz, AC-only, 15- or 20-amp fused electrical supply with a fuse or circuit breaker. A time-delay fuse or time-delay circuit breaker is recommended. It is recommended that a separate circuit serving only this microwave oven be provided.


VENTING REQUIREMENTS

A $3\frac{1}{4}$ " x 10" (8.3 x 25.4 cm) rectangular or 6" (15.2 cm) round vent should be used. The total length of the vent system including straight vent, elbow(s), transitions and wall or roof caps must not exceed the equivalent of 140 ft (42.7 m) for either type of vent. For best performance, use no more than three 90° elbows. To calculate the length of the system you need, add the equivalent length for each vent piece used in the system. See the following examples:




- A. Rectangular to round transition piece: $3\frac{1}{4}$ " x 10" to 6" = 5 ft (8.3 x 25.4 cm to 15.2 cm = 1.5 m)
 B. Roof cap: $3\frac{1}{4}$ " x 10" = 24 ft (8.3 x 25.4 cm = 7.3 m)
 C. 90° elbow: $3\frac{1}{4}$ " x 10" = 25 ft (8.3 x 25.4 cm = 7.6 m)
 D. 90° elbow: 6" = 10 ft (15.2 cm = 3 m)
 E. Wall cap: $3\frac{1}{4}$ " x 10" = 40 ft (8.3 x 25.4 cm = 12.2 m)
 F. 45° elbow: 6" = 5 ft (15.2 cm = 1.5 m)
 G. 90° flat elbow: $3\frac{1}{4}$ " x 10" = 10 ft (8.3 x 25.4 cm = 3 m)


6" (15.2 cm) vent system = 73 ft (22.2 m) total



$3\frac{1}{4}$ " x 10" (8.3 x 25.4 cm) vent system = 73 ft (22.2 m) total




PRODUCT DIMENSIONS



CABINET OPENING DIMENSIONS


The grounded 3-prong outlet must be inside the upper cabinet.



*30" (76.2 cm) is typical for 66" (167.6 cm) installation height. Exact dimensions may vary depending on type of range/cooktop below.

Rectangular to Round Transition for Roof Venting

NOTE: The minimum 3" (7.6 cm) clearance must exist between the top of the microwave oven and the rectangular to round transition piece so that the damper can open freely and fully.



- A. Roof cap
 B. 6" (15.2 cm) min. diameter round vent
 C. Elbow (for wall venting only)
 D. Wall cap
 E. $3\frac{1}{4}$ " x 10" to 6" (8.3 x 25.4 cm to 15.2 cm) rectangular to round transition piece
 F. Vent extension piece, at least 3" (7.6 cm) high