


ZLINE

ATTAINABLE LUXURY[®]



Installation and User Manual

SHOWER SYSTEM WITH RAINSYNC[™] EMERALD BAY MODELS

zlinekitchen.com



ZLINE Kitchen and Bath provides Attainable Luxury, where the kitchen and bath of your dreams is never out of reach. Through our unique designs and unparalleled quality, we're dedicated to providing you an elevated experience in the heart of your home. With an endless selection of features and finishes, our inspiration is your reality.

ZLINE
ATTAINABLE LUXURY®



ZLINE is fueled by a passion for innovation; A relentless pursuit of bringing the highest end luxury designs and professional features into everyone's homes.

Because we continually strive to improve our products, we may change specifications and designs without prior notice.

Scan the QR code to view the most up-to-date version of the Installation Manual and User Manual.

 **WARNING:** This product can expose you to chemicals including nickel, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

TABLE OF CONTENTS

IMPORTANT SAFETY INSTRUCTIONS..... 1

 Before Installation. 1

 Tools Needed 2

2 POINT SHOWER SYSTEM..... 3

 Before Installation. 3

 Installation. 5

3 POINT SHOWER SYSTEM..... 15

 Before Installation. 15

 Installation. 17

CARE AND MAINTENANCE..... 31

TROUBLESHOOTING..... 32

WARRANTY..... 33

IMPORTANT SAFETY INSTRUCTIONS

BEFORE INSTALLATION

- Make sure that the cold and hot water lines are turned off.
- Wrap all threaded connections with plumber's tape. Always wrap in a clockwise direction.
- Cover your drain to avoid losing parts.
- Do not disassemble the main system body, as it has been installed and commissioned correctly and precisely before delivery to the factory.
- To keep the system from jamming, flush the water pipe before installation.

Operating conditions: Working pressure at 0.05 MPa–1.0 MPa (including cold and hot water pressure) with applicable water temperature: 39 °F–194 °F (4 °C–90 °C).

- If soldering the water connections when installing the system, remove the O-rings, cartridges, and washers before applying any heat.
- Protect your eyes when cutting or soldering.
- Do not over tighten screws/nuts. Finger tighten, then use a wrench/screwdriver to tighten the fixing screw/nut until snug.

IMPORTANT SAFETY INSTRUCTIONS

TOOLS NEEDED

- Wrench
- Screwdriver
- Hammer
- Drill
- Allen/hex key
 - **NOTE:** Three point shower systems come with 3 Allen/hex keys:
 - Small: Used to attach the handles
 - Medium: Used to adjust the valve stems
 - Large: Used to adjust the valve stems for the body jets
- Plumber's tape

TIME REQUIRED: +/- 120 minutes

LEGEND



Hot water



Cold water



Torch




Warning



Plumber's tape

2 POINT SHOWER SYSTEM


BEFORE INSTALLATION



- | | |
|------------------|---------------------|
| 1. Flange cover | 9. Screw |
| 2. Shower arm | 10. Diverter handle |
| 3. Shower head | 11. Handle |
| 4. Valve body | 12. Flange cover |
| 5. Faceplate | 13. Angle valve |
| 6. Stem extender | 14. Shower rail |
| 7. Washer | 15. Hand sprayer |
| 8. Valve stem | 16. Hose |


2 POINT SHOWER SYSTEM

BEFORE INSTALLATION



2 POINT SHOWER SYSTEM


INSTALLATION




Connect the water lines to the rough in valve. If using a threaded connection wrap plumber's tape in a clockwise direction and tighten the connection with a wrench to ensure there are no leaks. If using a soldered water line connection, remove the cartridges and any O-rings to prevent damage due to heat.

After removing the O-rings and cartridges, solder the hot and cold water line connections to the rough in valve.

2 POINT SHOWER SYSTEM INSTALLATION





Turn on the water supply valves for 30 seconds to flush any debris or contaminants from the lines and valves.



Reassemble the valve body. Make sure that the set screw in the thermostatic valve is installed fully. Otherwise, it may not fit correctly.

2 POINT SHOWER SYSTEM

INSTALLATION




Using the minimum and maximum depth markings on the valve cover, ensure that the rough in valve is installed at an acceptable depth to prevent the finished wall or tiles from interfering with the rest of the installation process.

Use a screwdriver to remove the plastic cover from the rough in valve.

2 POINT SHOWER SYSTEM

INSTALLATION





Secure the valve stems onto the valves, then thread the stem extenders onto the valve body.

Remove the film from the adhesive on the faceplate and install onto the rough in valve.

2 POINT SHOWER SYSTEM

INSTALLATION




Place the flange over the exposed water line connection, then thread the shower arm onto the connection. Apply plumber's tape in a clockwise direction to prevent leaks.


Thread the shower head to the shower arm using the threaded connection.

2 POINT SHOWER SYSTEM

INSTALLATION




Thread the flange cover onto the exposed water line. Apply plumber's tape in a clockwise direction to prevent leaks.




Use a tape measure, level, and pencil to mark where the holes for the shower rail will be drilled. Use a 1/4" bit to drill the holes. Use the wall anchors as necessary.

2 POINT SHOWER SYSTEM INSTALLATION




Install the shower rail mounting brackets using the provided screws and a screwdriver.




Slide the shower rail onto the mounting brackets and use a hex key to tighten the set screws to secure the rail into place.

2 POINT SHOWER SYSTEM INSTALLATION



Connect the hand sprayer to the hose and the hose to the water supply using the threaded connections and plumber's tape. Ensure that the handle is threaded onto the hose completely.



Slide the O-ring and handle base onto the valve. Ensure that the handle and valve are aligned correctly by adjusting the valve position as needed. Remove the handle from the handle base to access the set screw.

13








Diagram of the 24-pin connector for the 24-pin SCSI interface. The diagram shows a circular connector with two rows of pins. The top row is labeled "Accessory 1" and the bottom row is labeled "Accessory 2". A central pin is labeled "Off". A 90-degree angle is indicated between the two rows of pins.

Review the diagram to understand the hot, cold, and open settings.


2 POINT SHOWER SYSTEM

INSTALLATION



3 POINT SHOWER SYSTEM


BEFORE INSTALLATION



- | | |
|------------------|-----------------------|
| 1. Flange cover | 10. Diverter handle |
| 2. Shower arm | 11. Handle |
| 3. Shower head | 12. Flange cover |
| 4. Valve body | 13. Angle valve |
| 5. Faceplate | 14. Shower rail |
| 6. Stem extender | 15. Hand sprayer |
| 7. Washer | 16. Hose |
| 8. Valve stem | 17. Built-in body jet |
| 9. Screw | |


3 POINT SHOWER SYSTEM

BEFORE INSTALLATION



3 POINT SHOWER SYSTEM

INSTALLATION




Connect the water lines to the rough in valve. If using a threaded connection wrap plumber's tape in a clockwise direction and tighten the connection with a wrench to ensure there are no leaks. If using a soldered water line connection, remove the cartridges and any O-rings to prevent damage due to heat.


After removing the O-rings and cartridges, solder the hot and cold water line connections to the rough in valve.

3 POINT SHOWER SYSTEM

INSTALLATION





Turn on the water supply valves for 30 seconds to flush any debris or contaminants from the lines and valves.



Reassemble the valve body. Make sure that the set screw in the thermostatic valve is installed fully. Otherwise, it may not fit correctly.

3 POINT SHOWER SYSTEM

INSTALLATION




Using the minimum and maximum depth markings on the valve cover, ensure that the rough in valve is installed at an acceptable depth to prevent the finished wall or tiles from interfering with the rest of the installation process.

Use a screwdriver to remove the plastic cover from the rough in valve.

3 POINT SHOWER SYSTEM

INSTALLATION




Secure the valve stems onto the valves, then thread the sleeves onto the valve body.

Remove the film from the adhesive on the faceplate and install onto the rough in valve.

3 POINT SHOWER SYSTEM

INSTALLATION




Place the flange over the exposed water line connection, then thread the shower arm onto the connection. Apply plumber's tape in a clockwise direction to prevent leaks.


Thread the shower head to the shower arm using the threaded connection.

3 POINT SHOWER SYSTEM

INSTALLATION




Thread the flange cover onto the exposed water line. Apply plumber's tape in a clockwise direction to prevent leaks.




Use a tape measure, level, and pencil to mark where the holes for the shower rail will be drilled. Use a 1/4" bit to drill the holes. Use the wall anchors as necessary.

3 POINT SHOWER SYSTEM

INSTALLATION




Install the shower rail mounting brackets using the provided screws and a screwdriver.



Slide the shower rail onto the mounting brackets and use a hex key to tighten the set screws to secure the rail into place.

3 POINT SHOWER SYSTEM

INSTALLATION





Connect the hand sprayer to the hose and the hose to the water supply using the threaded connections and plumber's tape. Ensure that the handle is threaded onto the hose completely.

Use this diagram to understand the placement of the water pipe.

3 POINT SHOWER SYSTEM

INSTALLATION




Thread the body jet adapter into the water supply using a hex key. Apply plumber's tape in a clockwise direction to prevent leaks. Cut the exposed pipe to an appropriate length to allow the body jet to sit flush with the wall.


Slide the plastic cover over the exposed pipe.

3 POINT SHOWER SYSTEM

INSTALLATION




Slide the cover plate over the pipe into the cover from the last step.




Use a hex key to thread the connector onto the exposed pipe.

3 POINT SHOWER SYSTEM

INSTALLATION




Install the main body as shown in the diagram. Pay attention to alignment position.




Lock the main body on the connector with the M4 x 20 Screws.

3 POINT SHOWER SYSTEM

INSTALLATION




Install the nozzle plate onto the main body and secure in place with the M4 x 12 screws.






Install the front plate onto the nozzle plate by aligning the locking clip. If aligned properly, the front plate should clip onto the nozzle plate.

3 POINT SHOWER SYSTEM INSTALLATION



Assemble the remaining body jets and thread them into the water supply connections.



3 POINT SHOWER SYSTEM


INSTALLATION

32




Press the security button and turn the handle counterclockwise until stopped.

33



With the handle still turned to its maximum, tighten the set screw with the help of a hex key, securing the handle.



Review the diagram to understand the settings.

CARE AND MAINTENANCE

CARE AND MAINTENANCE

To keep the product clean and shining, follow the steps below:

1. Rinse clean with water and dry with a soft cloth.
2. Do not clean with soaps, acid, polish, abrasives, or harsh cleaners.
3. Do not use cloths with a coarse surface.

TROUBLESHOOTING

PROBLEM	POSSIBLE CAUSE	SOLUTIONS
There is leakage under the handle.	The locking nut has come loose.	Unscrew the lever on the handle by hand. Loosen set screw with an Allen/hex key. Remove the handle and unscrew cap by hand. Tighten locking nut with an adjustable wrench.
Water will not shut off completely.	Cartridge may be defective.	Unscrew the lever on the handle by hand. Loosen set screw with an Allen/hex key. Remove the handle and unscrew cap by hand. Unscrew the locking nut with an adjustable wrench. Remove ceramic disc cartridge. Check for cracks.
There is a leak between the spray head and the hose.	The spray head may be loose or the washer is not seated correctly in the hose connection.	Tighten the spray head by hand until snug. Make sure the washer is seated correctly.

WARRANTY

COVERAGE

ZLINE Kitchen and Bath ("ZLINE") plumbing products have a limited lifetime warranty from the original purchase date for the original purchaser of the product.

ZLINE warranty periods begin from the original date of product delivery and solely cover the original purchaser of the product, delivered new and in its original carton. ZLINE will provide free-of-charge, non-consumable replacement parts for the components that failed due to manufacturing defects. It is the responsibility of the customer to install all replacement parts, as ZLINE does not perform service repairs on its plumbing products.

ZLINE's liability is limited to the original purchase price of the product. Additional injuries, losses, damages, or other inconveniences caused by product malfunction or defects in materials are not covered under the terms of this warranty.

TERMS

ZLINE warranties apply only to the original purchaser of a ZLINE product installed for normal residential use. This is defined as a single-family, residential dwelling in a non-commercial setting. Any warranty claim stemming from installation, operation, or any other use within a commercial setting is not covered under this limited warranty.

Commercial settings include, but are not limited to: schools, churches, hotels, restaurants, vacation rentals such as Airbnb, daycare centers, private clubs, fire stations, common areas in multi-family dwellings, nursing homes, food service locations, and institutional food service locations such as hospitals or correctional facilities.

This warranty is non-transferable and will not under any circumstance be extended based on the date of installation — the warranty period takes effect from the date of delivery and only covers the original purchaser. The warranty applies only to products installed in the contiguous United States and the District of Columbia.

Out-of-pocket payments will not be reimbursed for replacement parts unless prior approval is received from ZLINE. Unapproved out-of-pocket payments for parts will not be reimbursed. Out-of-pocket payments for any type of service will not be reimbursed, as ZLINE does not perform service repairs on its plumbing products. All warranty procedures must be followed to maintain warranty coverage.

WARRANTY

If ZLINE is unable to replace the defective part after a reasonable number of attempts, ZLINE reserves the right to offer to replace the product or provide the original purchaser a full refund of the purchase price of the product (not including installation, removal, or other charges that were not included in the original purchase price).

The original purchaser of the product must provide the original proof of purchase, including the purchase date, when filing a claim to obtain replacement parts or refunds. Additionally, the original purchaser of the product must provide the serial number of the product when filing a claim to obtain replacement parts or refunds.

This warranty shall not apply to any ZLINE product in which the original factory serial number has been removed, altered, or cannot be readily determined for any reason. Further, ZLINE is not responsible for damage resulting from, but not limited to: shipment, delivery, or improper installation; negligence or improper maintenance, misuse, or abuse of the product; unauthorized alteration, modification, or tampering with the product; accident, fire, floods, pest infestations, pandemics, natural disasters, or any other unpreventable or unexplained acts of nature, commonly referred to as “acts of God”; water leaks or water damages caused by improper water supply or water connections associated with installation or disassembly of the product; and service to correct installation not in accordance with the instructions contained in ZLINE’s product manuals and/or with local government codes.

Additionally, this plumbing warranty does not apply to aesthetic damage, scratches, or natural wear caused by normal use; second-hand, open box products, or products purchased from an unauthorized retailer; consumable parts including, but not limited to, rough in valves, aerators, diverter handles, sprayers, spouts, hoses, and flange covers; and damages, problems, or any type of performance-related issues stemming from alteration or tampering with the product, including, but not limited to, painting stainless steel, black stainless, Satin Stainless Steel, or any other finishes or any portion of the product’s interior or exterior.

Information contained within ZLINE’s installation and user manuals, in addition to product information included on ZLINE’s website and all related digital listings, do not cover every possible condition and situation that may occur during the installation or operation of ZLINE products.

WARRANTY

ZLINE reserves the right to make changes at any time to its products when considered safe, necessary, and useful. Always check the ZLINE website for the most up-to-date version of its product manuals: www.zlinekitchen.com/pages/manuals.

Do not install or operate any ZLINE product if it has missing or broken parts or if it arrives damaged due to shipping. If ZLINE products arrive damaged, contact ZLINE Customer Experience at 1-614-777-5004 for help. Failure to report a damaged appliance prior to installation or operation may void the warranty. ZLINE does not perform service repairs on its plumbing products. ZLINE disclaims responsibility for damage or injury caused by improper installation or use of any of its products.

WARRANTY



SERVICE

For warranty service, please contact our Customer Service team at 1-614-777-5004 or visit www.zlinekitchen.com/contact to utilize our online Customer Experience Portal.



Scan the QR code to view the most up-to-date version of our Installation and User Manual.



Need to purchase a part or accessory for your ZLINE product?
Visit www.zlineparts.com, ZLINE's official parts distribution partner.

3.0.1

zlinekitchen.com

1-614-777-5004

contact@zlinekitchen.com

ZLINE
ATTAINABLE LUXURY®